

NSX-T Data Center Upgrade Guide

10 OCT 2024

VMware NSX-T Data Center 3.2

You can find the most up-to-date technical documentation on the VMware by Broadcom website at:

<https://docs.vmware.com/>

VMware by Broadcom
3401 Hillview Ave.
Palo Alto, CA 94304
www.vmware.com

Copyright © 2024 Broadcom. All Rights Reserved. The term “Broadcom” refers to Broadcom Inc. and/or its subsidiaries. For more information, go to <https://www.broadcom.com>. All trademarks, trade names, service marks, and logos referenced herein belong to their respective companies.

Contents

| | |
|---|-----------|
| Upgrading NSX-T Data Center | 5 |
| 1 NSX-T Data Center Upgrade Checklist | 6 |
| 2 Preparing to Upgrade NSX-T Data Center | 7 |
| Operational Impact of the NSX-T Data Center Upgrade | 7 |
| Supported Upgrade Paths | 9 |
| Pre-Upgrade Tasks | 10 |
| Upgrading Your Host OS | 11 |
| Upgrade ESXi Host | 12 |
| Upgrade Ubuntu Host | 13 |
| Upgrade CentOS Host | 14 |
| Upgrade RHEL Host | 15 |
| Upgrade SLES Host | 15 |
| Verify the Current State of NSX-T Data Center | 16 |
| Download the NSX-T Data Center Upgrade Bundle | 17 |
| 3 Upgrading NSX-T Data Center | 18 |
| Upgrade the Upgrade Coordinator | 19 |
| Upgrade NSX Edge Cluster | 21 |
| Configuring and Upgrading Hosts | 23 |
| Configure Hosts | 23 |
| Manage Host Upgrade Unit Groups | 27 |
| Upgrade Hosts | 28 |
| Upgrade a vSphere Lifecycle Manager-enabled Cluster | 30 |
| Upgrade Hosts Manually | 31 |
| Upgrade Management Plane | 33 |
| 4 Upgrading NSX Cloud Components | 35 |
| Regenerate the Public Cloud Permissions | 36 |
| Upgrade the Upgrade Coordinator from CSM | 36 |
| Download the NSX Cloud Upgrade Bundle | 36 |
| Upgrade the Upgrade Coordinator in CSM | 37 |
| Upgrade the Upgrade Coordinator from NSX Manager | 37 |
| Upgrade NSX Tools and PCG | 37 |
| Skip Upgrading NSX Tools | 39 |
| Troubleshooting NSX Tools Upgrade on Windows Workload VMs | 40 |
| Troubleshooting NSX Tools Upgrade on Linux Workload VMs | 41 |

Upgrade NSX Manager 42

Upgrade CSM 42

5 Post-Upgrade Tasks 45

Verify the Upgrade 45

6 Troubleshooting Upgrade Failures 48

Collect Support Bundles 48

Upgrade Fails Due to a Timeout 50

Upgrade Fails Due to Insufficient Space in Bootbank on ESXi Host 50

Unable to Upgrade Host Placed in NSX Maintenance Mode 51

Failure to Upload the Upgrade Bundle 51

Backup and Restore During Upgrade 52

Loss of Controller Connectivity after Host Upgrade 52

In-place Upgrade Fails 53

Upgrade Coordinator User Interface is Inaccessible 53

NSX Manager User Interface is Inaccessible During Upgrade 54

7 Upgrading your NSX Federation Deployment 55

Upgrading NSX-T Data Center

The *NSX-T Data Center Upgrade Guide* provides step-by-step information about upgrading the NSX-T Data Center components, which include the data plane, control plane, and management plane with minimum system downtime.

Intended Audience

This information is intended for anyone who wants to upgrade to NSX-T Data Center 3.2. The information is written for experienced system administrators who are familiar with virtual machine technology, virtual networking, and security concepts and operations.

VMware Technical Publications Glossary

VMware Technical Publications provides a glossary of terms that might be unfamiliar to you. For definitions of terms as they are used in VMware technical documentation, go to <https://www.vmware.com/topics/glossary>.

Related Documentation

You can find the VMware NSX® Intelligence™ documentation at <https://docs.vmware.com/en/VMware-NSX-Intelligence/index.html>. The NSX Intelligence 1.0 content was initially included and released with the NSX-T Data Center 2.5 documentation set.

NSX-T Data Center Upgrade Checklist

1

Use the checklist to track your work on the upgrade process.

Table 1-1. Upgrade NSX-T Data Center

| Task | Instructions |
|---|---|
| Review the known upgrade problems and workaround documented in the NSX-T Data Center release notes. | See the <i>NSX-T Data Center Release Notes</i> . |
| Follow the system configuration requirements and prepare your infrastructure. | See the system requirements section of the <i>NSX-T Data Center Installation Guide</i> . |
| Evaluate the operational impact of the upgrade. | See Operational Impact of the NSX-T Data Center Upgrade . |
| Upgrade your supported hypervisor. | See Upgrading Your Host OS . |
| If you have an earlier version of NSX Intelligence installed, upgrade NSX Intelligence first. | See <i>Activating and Upgrading VMware NSX Intelligence</i> for version 3.2 or later at https://docs.vmware.com/en/VMware-NSX-Intelligence/index.html . |
| Complete the Pre-Upgrade Tasks. | See Pre-Upgrade Tasks . |
| Verify that the NSX-T Data Center environment is in a healthy state. | See Verify the Current State of NSX-T Data Center . |
| Download the latest NSX-T Data Center upgrade bundle. | See Download the NSX-T Data Center Upgrade Bundle . |
| If you are using NSX Cloud for your public cloud workload VMs, upgrade NSX Cloud components. | See Chapter 4 Upgrading NSX Cloud Components . |
| Upgrade your upgrade coordinator. | See Upgrade the Upgrade Coordinator . |
| Upgrade the NSX Edge cluster. | See Upgrade NSX Edge Cluster . |
| Upgrade the hosts. | See Configuring and Upgrading Hosts . |
| Upgrade the Management plane. | See Upgrade Management Plane . |
| Post-upgrade tasks. | See Verify the Upgrade . |
| Troubleshoot upgrade errors. | See Chapter 6 Troubleshooting Upgrade Failures . |

Preparing to Upgrade NSX-T Data Center

2

You must prepare your infrastructure and follow the task sequence provided in the checklist for the upgrade process to be successful.

You can perform the upgrade process in a maintenance time frame defined by your company. You can, for example, upgrade only one of the components and upgrade the other NSX-T Data Center components later, during another maintenance time frame. Ensure that you follow the upgrade order while upgrading the components: NSX Edge cluster > Hosts > Management plane.

Read the following topics next:

- [Operational Impact of the NSX-T Data Center Upgrade](#)
- [Supported Upgrade Paths](#)
- [Pre-Upgrade Tasks](#)
- [Upgrading Your Host OS](#)
- [Verify the Current State of NSX-T Data Center](#)
- [Download the NSX-T Data Center Upgrade Bundle](#)

Operational Impact of the NSX-T Data Center Upgrade

The duration for the NSX-T Data Center upgrade process depends on the number of components you have to upgrade in your infrastructure. It is important to understand the operational state of NSX-T Data Center components during an upgrade.

The upgrade process is as follows:

NSX Edge cluster > Hosts > Management plane.

NSX Edge Cluster Upgrade

| During Upgrade | After Upgrade |
|--|--|
| <ul style="list-style-type: none"> ■ During the NSX Edge upgrade, you might experience the following traffic interruption: <ul style="list-style-type: none"> ■ North-south datapath is affected if the NSX Edge is part of the datapath. ■ East-west traffic between tier-1 routers using NSX Edge firewall, NAT, or load balancing. ■ Temporary Layer 2 and Layer 3 interruption. ■ Configuration changes are not blocked on NSX Manager but might be delayed. | <ul style="list-style-type: none"> ■ Configuration changes are allowed. ■ Upgraded NSX Edge cluster is compatible with the older versions of the Management plane and the hosts. ■ New features introduced in the upgrade are not configurable until the Management plane is upgraded. ■ Run post checks to make sure that the upgraded NSX Edge cluster and NSX-T Data Center do not have any problems. |

Hosts Upgrade

| During Upgrade | After Upgrade |
|--|---|
| <ul style="list-style-type: none"> ■ For standalone ESXi hosts or ESXi hosts that are part of a disabled DRS cluster, place hosts in maintenance mode. For ESXi hosts that are part of a fully enabled DRS cluster, if the host is not in maintenance mode, the upgrade coordinator requests the host to be put in maintenance mode. The vSphere DRS tool migrates the VMs to another host in the same cluster during the upgrade and places the host in maintenance mode. ■ For ESXi host, for an in-place upgrade you do not need to power off the tenant VMs. ■ For a KVM host, for an in-place upgrade you do not need to power off the VMs. For a maintenance mode upgrade, power off the VMs. ■ Configuration changes are allowed on NSX Manager. ■ You may experience brief disruption in traffic during in-place upgrade of the ESXi hosts. For critical applications that cannot handle packet loss, maintenance mode upgrade is recommended. | <ul style="list-style-type: none"> ■ Power on or return the tenant VMs of standalone ESXi hosts or ESXi hosts that are part of a disabled DRS cluster that were powered off before the upgrade. ■ New features introduced in the upgrade are not configurable until the Management plane is upgraded. ■ Run post checks to make sure that the upgraded hosts and NSX-T Data Center do not have any problems. |

Note If an ENS host switch is configured from NSX-T Data Center 3.0 onwards, flow cache is populated and FPO offloads it to NIC (if it supports). In this case, the "flow-table dump" shows the "OL" flag. If you upgrade to NSX-T Data Center 3.2, you might not see the "OL" flags due to inclusion of L4 info in flow cache as model 1 NICs do not support flow cache offloading.

Limitations on In-Place Upgrade

For ESXi hosts with version 7.0 and later, when upgrading from NSX-T Data Center 3.1 or later, in-place upgrade is not supported in the following scenarios:

- You are upgrading a vLCM-enabled cluster.
- More than 1000 vNICs are configured on the ESXi host and the VM's vNICs connect to a single switch, either N-VDS or VDS. If the host has multiple switches for NSX-T Data Center, this vNIC limit is per switch.
- Layer 7 firewall rules or Identity Firewall rules are enabled.

- Service Insertion has been configured to redirect north-south traffic or east-west traffic. See *Security* in the *NSX-T Data Center Administration Guide* for information on uninstalling service insertion.
- A VProbe-based packet capture is in progress.
- The `nsx-cfgagent` service is not running on the host.
- IDS/IPS is enabled for your NSX-T Data Center environment.

For ESXi hosts with versions earlier than 7.0, in-place upgrade of a host is not supported in the following scenarios:

- You are upgrading a vLCM-enabled cluster.
- More than one N-VDS switch is configured on the host.
- More than 1000 vNICs are configured on the ESXi host and the VM's vNICs connect to a single switch, either N-VDS or VDS. If the host has multiple switches for NSX-T Data Center, this vNIC limit is per switch.
- ENS is configured on the host N-VDS switch.
- vSAN(with LACP) is configured on the host N-VDS switch.
- Layer 7 firewall rules or Identity Firewall rules are enabled.
- VMkernel interface is configured on the overlay network.
- Service Insertion has been configured to redirect north-south traffic or east-west traffic. See *Security* in the *NSX-T Data Center Administration Guide* for information on uninstalling service insertion.
- A VProbe-based packet capture is in progress.
- IDS/IPS is enabled for your NSX-T Data Center environment.

Management Plane Upgrade

| During Upgrade | After Upgrade |
|--|---|
| <ul style="list-style-type: none"> ■ Do not make any configuration changes during the Management plane upgrade. ■ API service is momentarily unavailable. ■ User interface is unavailable for a short period. | <ul style="list-style-type: none"> ■ Configuration changes are allowed. ■ New features introduced in the upgrade are configurable. ■ For NSX-T Data Center 3.0, you need a valid license to use licensed features like T0, T1, Segments, and NSX intelligence. ■ From the Upgrade Coordinator, verify that the upgrade process has completed. Perform configuration tasks only after the upgrade process is complete. |

Supported Upgrade Paths

The supported upgrade paths for the NSX-T Data Center product versions.

Adhere to the following upgrade paths for each NSX-T Data Center release version.

- NSX-T Data Center 3.0.x > NSX-T Data Center 3.2.x.
- NSX-T Data Center 3.1.x > NSX-T Data Center 3.2.x.

Table 2-1. Hypervisor Support

| NSX-T Data Center 3.2 | NSX-T Data Center 3.1 | NSX-T Data Center 3.0 |
|---|--|---|
| Supported vSphere Hypervisor (ESXi) | Supported vSphere Hypervisor (ESXi) | Supported vSphere Hypervisor (ESXi) |
| Ubuntu: 20.04, 18.04 | Ubuntu: 20.04, 18.04 | Ubuntu: 18.04, 16.04.2 LTS (Kernel version 4.4.0.x) |
| RHEL: 8.4, 8.2, 7.9 | RHEL: 8.2, 7.7 RHEL: 7.9 (Starting NSX-T Data Center 3.1.1) | RHEL: 7.7, 7.6 |
| CentOS: 8.4, 7.9 | CentOS: 8.2, 7.7 | CentOS: 7.7, 7.6 |
| SUSE Linux Enterprise Server (SLES): 12 sp4 | SUSE Linux Enterprise Server (SLES): 12 sp4 | SUSE Linux Enterprise Server (SLES): 12 sp4, 12 sp3 |

Table 2-2. Bare Metal Server Support

| NSX-T Data Center 3.2 | NSX-T Data Center 3.1 | NSX-T Data Center 3.0 |
|---|---|---|
| Ubuntu: 18.04, 16.04 | Ubuntu: 18.04, 16.04 | Ubuntu: 18.04, 16.04 |
| RHEL: 8.3, 8.0, 7.9, 7.8, 7.7, 7.6 | RHEL: 7.8, 7.7, 7.6 RHEL: 7.9 (Starting NSX-T Data Center 3.1.2.1) | RHEL: 7.7, 7.6 |
| CentOS: 8.3, 8.0, 7.9, 7.8, 7.7, 7.6 | CentOS: 7.8, 7.7, 7.6 CentOS: 7.9 (Starting NSX-T Data Center 3.1.2.1) | CentOS: 7.7, 7.6 |
| SUSE Linux Enterprise Server (SLES): 12 sp4, 12 sp3 | SUSE Linux Enterprise Server (SLES): 12 sp4, 12 sp3 | SUSE Linux Enterprise Server (SLES): 12 sp4, 12 sp3 |
| OEL: 7.9, 7.8, 7.7, 7.6 | OEL: 7.6, 7.7 OEL: 7.8, 7.9 (Starting NSX-T Data Center 3.1.2.1) | OEL: 7.6, 7.7 (Starting NSX-T Data Center 3.0.2) |
| Windows Server: 2016, 2019 | Windows Server: 2016, 2019 | Windows Server: 2016 |

Pre-Upgrade Tasks

Before you upgrade NSX-T Data Center, perform the pre-upgrade tasks to ensure that the upgrade is successful.

Procedure

- 1 For upgrade to NSX-T Data Center 3.2.0.1, run the NSX Upgrade Evaluation Tool before you begin the upgrade process. The tool is designed to ensure success by checking the upgrade readiness of your NSX Manager nodes. For more information on the tool, see the VMware knowledge base article at <https://kb.vmware.com/s/article/87379>.

For upgrade to NSX-T Data Center version 3.2.2 and later, the checks performed by the Upgrade Evaluation Tool are run by NSX-T Data Center as part of the upgrade pre-check.

- 2 Ensure that your transport node profiles have the appropriate transport zones added to them. NSX Manager may not display the list of transport node profiles if any of the transport node profiles do not have transport zones added to them.
- 3 Ensure that you backup the NSX Manager before you start the upgrade process. See the *NSX-T Data Center Administration Guide*.
- 4 Ensure that your host OS is supported for NSX Manager. See *Supported Hosts for NSX Managers* in the *NSX-T Data Center Administration Guide*
- 5 Disable automatic backups before you start the upgrade process. See the *NSX-T Data Center Administration Guide* for more information on configuring backups.
- 6 Terminate any active SSH sessions or local shell scripts that may be running on the NSX Manager or the NSX Edge nodes, before you begin the upgrade process.
- 7 Ensure that the appropriate communication ports are open from the Transport and Edge nodes to the NSX Managers. For more information on ports, see <https://ports.esp.vmware.com/home/NSX-T-Data-Center>.

NSX Cloud Note NSX Cloud supports communication on port 80 between the Cloud Service Manager appliance installed on-premises with the NSX Public Cloud Gateway installed in your public cloud VPC/VNet.

- 8 You need a valid license to use licensed features like TO, T1, Segments, and NSX intelligence. Ensure that you have a valid license.
- 9 For upgrade to NSX-T Data Center 3.2.0 and 3.2.0.1, see <https://kb.vmware.com/s/article/87765> for information on preparing your Edge VMs for upgrade.
- 10 Ensure that you have configured the SFTP server and are using a complex passphrase.
- 11 Delete all expired user accounts before you begin upgrade. Upgrade for NSX-T Data Center on vSphere fails if your exception list for vSphere lockdown mode includes expired user accounts. For more information on accounts with access privileges in lockdown mode, see *Specifying Accounts with Access Privileges in Lockdown Mode* in the *vSphere Security Guide*.

Upgrading Your Host OS

To avoid problems during the host upgrade, your host OS must be supported in NSX-T Data Center.

If the version of your host OS is unsupported, you can manually upgrade the host OS to the supported version. See [Supported Upgrade Paths](#).

For RHEL, CentOS, Ubuntu, and SLES host upgrade instructions, refer to the host web site.

Upgrade ESXi Host

If your ESXi host is unsupported, manually upgrade your ESXi host to the supported version.

Prerequisites

- Verify that the ESXi host is supported. See [Supported Upgrade Paths](#).
- Ensure that you have the supported version of vCenter Server. See [Product Interoperability Matrix](#).

Procedure

- ◆ Upgrade the ESXi host using one of the following options.

- Perform the upgrade from the ESXi CLI:

- a Place your ESXi host in maintenance mode.
- b Run the following command from the ESXi CLI:

```
esxcli software profile update --depot <path-to-depot-file> ESXi-X.X.X-XXXXXX-
standard --allow-downgrades --no-sig-check
```

- c Download the NSX kernel module for VMware ESXi x.x.
- d Install the NSX kernel module.

```
esxcli software vib install -d <path_to_kernel_module_file> --no-sig-check
```

- e Reboot the ESXi host.
 - f Move your ESXi host out of maintenance mode.
- Upgrade ESXi in an offline environment using vSphere Update Manager:
 - a Log in to vCenter Server.
 - b Download and add the supported ESXi software depot to the image builder inventory.
 - c Download and add the NSX kernel module for VMware ESXi x.x to the image builder inventory.
 - d Create a customized software depot, create a new image profile, and select the packages from the software depots that you added to the image builder inventory.
 - e Export the image to ISO.
 - f Upload the installation ISO image to the vSphere Update Manager repository.

- g Create a baseline based on the uploaded ISO image in vSphere Update Manager, and attach it to a cluster.
- h Start the remediate process and wait for the upgrade process to complete.
- i Run the remediate process again if you see any upgrade failures.
- Perform the upgrade using a baseline group:
 - a Log in to vCenter Server.
 - b In the lifecycle manager, upload the ESXi x.x installation ISO and import the NSX kernel modules for VMware ESXi x.x .
 - c Create an upgrade baseline using the imported ESXi x.x installation ISO
 - d Create an extension baseline using the uploaded NSX kernel modules.
 - e Create a baseline group using the baselines you created in the preceding steps.
 - f Attach the baseline group to a cluster. Ensure the vmknics on the hosts have been configured. If the vmknics are configured to use DHCP, make sure the DHCP server is running.
 - g Start the remediate process and wait for the upgrade process to complete.
 - h Run the remediate process again if you see any upgrade failures.
- Starting NSX-T Data Center 3.1.1 and vSphere 7.0 update 1, for vSphere Lifecycle Manager-enabled clusters, you can upgrade your ESXi host along with NSX-T Data Center, using vSphere Lifecycle Manager.
 - a Upload the ESXi host image to vSphere Lifecycle Manager depot.
 - b Update the ESXi host version for the cluster image.
 - c From the NSX Manager UI, select **Stage in vSphere Lifecycle Manager** when configuring the host upgrade. See [Configure Hosts](#).
 - d Follow the steps in [Upgrade a vSphere Lifecycle Manager-enabled Cluster](#) to complete the upgrade.

Upgrade Ubuntu Host

If your Ubuntu host is unsupported, manually upgrade your Ubuntu host to the supported version.

Prerequisites

Verify that the Ubuntu host is supported. See [Supported Upgrade Paths](#).

Ubuntu requires the following dependencies for the LCP package and host components to work properly.

```
libunwind8, libgflags2v5, libgoogle-perftools4, traceroute, python3, python-mako,
python-simplejson, python-unittest2, python-yaml, python-netaddr, libprotobuf9v5, libboost-
chrono1.58.0, libgoogle-glog0v5, dkms, libboost-date-time1.58.0, libleveldb1v5, libsnappy1v5,
python-gevent, python-protobuf, ieee-data, libyaml-0-2, python-linecache2, python-traceback2,
libtcmalloc-minimal4, python-greenlet, python-markupsafe, libboost-program-options1.58.0,
libelf-dev
```

Procedure

- 1 Follow the instructions available on the Ubuntu web site to upgrade your host. Reboot the Ubuntu KVM host after the upgrade process has completed.
- 2 If you have an existing Ubuntu KVM host as a transport node, back up the `/etc/network/interfaces` file.
- 3 Download the NSX kernel module for Ubuntu x.x.
- 4 Install the NSX kernel module.

```
tar -xvf <path_to_kernel_module_file>
cd <folder_extracted_from_previous_step>
sudo dpkg -i *.deb
dpkg -i | grep nsx
```

Upgrade CentOS Host

If your CentOS host is unsupported, manually upgrade your CentOS host to the supported version.

Prerequisites

Verify that the CentOS host is supported. See [Supported Upgrade Paths](#).

CentOS requires the following dependencies for the LCP package and host components to work properly.

```
PyYAML, c-ares, libev, libunwind, libyaml, python3, python-beaker, python-gevent, python-
greenlet, python-mako, python-markupsafe, python-netaddr, python-paste, python-tempita
```

Procedure

- 1 Follow the instructions available on the CentOS web site to upgrade your host. Reboot the CentOS host after the upgrade process has completed.
- 2 Download the NSX kernel module for CentOS xx.x.

3 Install the NSX kernel module.

```
tar - xvf <path_to_kernel_module_file>
cd <folder_extracted_from_previous_step>
sudo yum install *.rpm
rpm -qa | grep nsx
```

Upgrade RHEL Host

If your RHEL host is unsupported, manually upgrade your RHEL host to the supported version.

Prerequisites

Verify that the RHEL host is supported. See [Supported Upgrade Paths](#).

RHEL requires the following dependencies for the LCP package and host components to work properly.

```
PyYAML, c-ares, libev, libunwind, libyaml, python3, python-beaker, python-gevent, python-greenlet, python-mako, python-markupsafe, python-netaddr, python-paste, python-tempita
```

Procedure

- 1 Follow the instructions available on the RHEL web site to upgrade your host. Reboot the RHEL host host after the upgrade process has completed.
- 2 Restart the NSX agent.


```
/etc/init.d/nsx-opsagent restart
```
- 3 Download the NSX kernel module for RHEL x.x.
- 4 Install the NSX kernel module.

```
tar - xvf <path_to_kernel_module_file>
cd <folder_extracted_from_previous_step>
sudo yum install *.rpm
rpm -qa | grep nsx
```

Upgrade SLES Host

If your SUSE Linux Enterprise Server (SLES) host is unsupported, manually upgrade your SLES host to the supported version.

Prerequisites

Verify that the SLES host is supported. See [Supported Upgrade Paths](#).

SLES requires the following dependencies for the LCP package and host components to work properly.

```
python3, python-simplejson, python-netaddr, python-PyYAML, lsb-release, libcap-progs
```

Procedure

- 1 Follow the instructions available on the SLES web site to upgrade your host. Reboot the SLES host after the upgrade process has completed.
- 2 Download the NSX kernel module for SLES x.x.
- 3 Install the NSX kernel module.

```
tar - xvf <path_to_kernel_module_file>
cd <folder_extracted_from_previous_step>
sudo rpm -ivh *.rpm
rpm -qa | grep nsx
```

- 4 (Optional) Restart the NSX agent.

```
/etc/init.d/nsx-opsagent restart
```

Verify the Current State of NSX-T Data Center

Before you begin the upgrade process, it is important to test the NSX-T Data Center working state. Otherwise, you cannot determine if the upgrade caused post-upgrade problems or if the problem existed before the upgrade.

Note Do not assume that everything is working before you start to upgrade the NSX-T Data Center infrastructure.

Procedure

- 1 Identify and record the administrative user IDs and passwords.
- 2 Verify that you can log in to the NSX Manager web user interface.
- 3 Check the **Dashboard**, system overview, host transport nodes, edge transport nodes, NSX Edge cluster, transport nodes, HA status of the edge, and all logical entities to make sure that all the status indicators are green, deployed, and do not show any warnings.
- 4 Validate North-South connectivity by pinging out from a VM.
- 5 Validate that there is an East-West connectivity between any two VMs in your environment.
- 6 Record BGP states on the NSX Edge devices.
 - `get logical-routers`
 - `vrf <vrf>`
 - `get bgp`
 - `get bgp neighbor`

Download the NSX-T Data Center Upgrade Bundle

The upgrade bundle contains all the files to upgrade the NSX-T Data Center infrastructure. Before you begin the upgrade process, you must download the correct upgrade bundle version.

You can also navigate to the upgrade bundle and save the URL. When you upgrade the upgrade coordinator, paste the URL so that the upgrade bundle is uploaded from the VMware download portal.

Procedure

- 1 Locate the NSX-T Data Center build on the [VMware download portal](#).
- 2 Navigate to the upgrade bundle file and click **Read More**.
- 3 Verify that the upgrade bundle filename extension ends with `.mub`.

The upgrade bundle filename has a format similar to `VMware-NSX-upgrade-bundle-ReleaseNumberNSXBuildNumber.mub`.

- 4 Download the NSX-T Data Center upgrade bundle to the same system you are using to access the NSX Manager user interface.

Upgrading NSX-T Data Center

3

After you finish the prerequisites for upgrading, your next step is to update the upgrade coordinator to initiate the upgrade process.

NSX Intelligence and NSX Application Platform Note For information about upgrading NSX Intelligence version 1.2.x and earlier to NSX Intelligence version 3.2 and later, see the *Activating and Upgrading VMware NSX Intelligence* documentation at <https://docs.vmware.com/en/VMware-NSX-Intelligence/index.html>.

For information about upgrading NSX Application Platform, see the *Deploying and Managing the VMware NSX Application Platform* documentation at <https://docs.vmware.com/en/VMware-NSX-T-Data-Center/index.html>.

After the upgrade, based on your input, the upgrade coordinator updates the hosts, NSX Edge cluster, and Management plane.

You can use REST APIs to upgrade your NSX-T Data Center appliance. Identify the NSX-T Data Center version you are upgrading to. Refer to the API guide with your product version in code.vmware.com to find the latest upgrade-related APIs.

Procedure

1 Upgrade the Upgrade Coordinator

The upgrade coordinator runs in the NSX Manager. It is a self-contained web application that orchestrates the upgrade process of hosts, NSX Edge cluster, NSX Controller cluster, and Management plane.

2 Upgrade NSX Edge Cluster

After the upgrade coordinator has been upgraded, based on your input, the upgrade coordinator updates the NSX Edge cluster, hosts, and the Management plane. Edge upgrade unit groups consist of NSX Edge nodes that are part of the same NSX Edge cluster. You can reorder Edge upgrade unit groups and enable or disable an Edge upgrade unit group from the upgrade sequence.

3 Configuring and Upgrading Hosts

You can upgrade your hosts using the upgrade coordinator.

4 Upgrade Management Plane

The upgrade sequence upgrades the Management Plane at the end. When the Management Plane upgrade is in progress, avoid any configuration changes from any of the nodes.

Upgrade the Upgrade Coordinator

The upgrade coordinator runs in the NSX Manager. It is a self-contained web application that orchestrates the upgrade process of hosts, NSX Edge cluster, NSX Controller cluster, and Management plane.

The upgrade coordinator guides you through the proper upgrade sequence. You can track the upgrade process and if necessary you can pause and resume the upgrade process from the user interface.

The upgrade coordinator allows you to upgrade groups in a serial or parallel order. It also provides the option of upgrading the upgrade units within that group in a serial or parallel order.

Prerequisites

Verify that the upgrade bundle is available. See [Download the NSX-T Data Center Upgrade Bundle](#).

Procedure

- 1 In the NSX Manager CLI, verify that the NSX-T Data Center services are running.

```
get service install-upgrade
```

If the services are not running, troubleshoot the problem. See the *NSX-T Data Center Troubleshooting Guide*.

- `get service install-upgrade` lists the IP address of the orchestrator node. See `Enabled on`.

You can also make the following API call to retrieve the IP address.

```
GET /api/v1/node/services/install-upgrade
```

Use this IP address throughout the upgrade process.

Note Ensure that you do not use any type of Virtual IP address or the FQDN to upgrade NSX-T Data Center.

- To change the orchestrator node, log in to the node that you want to set as an orchestrator node and run `set repository-ip`.

Note If in an NSX Federation environment, you are upgrading a Local Manager from the Global Manager and you have changed the orchestrator node of the Local Manager, this change takes some time to appear on the Global Manager UI.

- When the Management Plane upgrade is in progress, avoid any configuration changes from any of the nodes.
- 2 From your browser, log in as a local admin user to an NSX Manager at `https://nsx-manager-ip-address/login.jsp?local=true`.
 - 3 Select **System > Upgrade** from the navigation panel.
 - 4 Click **Proceed to Upgrade**.
 - 5 Navigate to the upgrade bundle `.mub` file by navigating to the downloaded upgrade bundle or pasting the download URL link.
 - Click **Browse** to navigate to the location you downloaded the upgrade bundle `.mub` file.
 - Paste the VMware download portal URL where the upgrade bundle `.mub` file is located.
 - 6 Click **Upload**.

Upgrading the upgrade coordinator might take 10–20 minutes, depending on your network speed. If the network times out, reload the upgrade bundle.

When the upload process finishes, the **Begin Upgrade** button appears.

- 7 Click **Begin Upgrade** to upgrade the upgrade coordinator.

Note Do not initiate multiple simultaneous upgrade processes for the upgrade coordinator.

The EULA appears.

- 8 Read and accept the EULA terms.
- 9 Accept the notification to upgrade the upgrade coordinator.
- 10 (Optional) If a patch release becomes available after the upgrade coordinator is updated, upload or add the URL of the latest upgrade bundle and upgrade the upgrade coordinator.
- 11 Click **Run Pre-Checks** to verify that all the NSX-T Data Center components are ready for upgrade.

This action checks for component connectivity, version compatibility, and component status among other environment readiness checks, for your current upgrade plan.

Note You must run the pre-checks when you change or reset your upgrade plan, or upload a new upgrade bundle.

- 12 (Optional) View the list of pre-checks that are performed with the API call `GET https://<nsx-manager>/api/v1/upgrade/upgrade-checks-info`.

- 13 Resolve any warning notifications to avoid problems during the upgrade.
 - a Click the Hosts notification next to **Pre-Checks** to see the warning details.
You might have to place some of the hosts in maintenance mode.
 - b Click the Edges notification next to **Pre-Checks** to see the warning details.
You might have to resolve connectivity problems.
 - c Click the Management Nodes notification next to **Pre-Checks** to see the warning details.
You can click **Download Pre-Check Results** to download a CSV file with details about pre-check errors for each component and their status.
- 14 (Optional) Click **Show Upgrade History** and view information about previous NSX Manager upgrades.

Upgrade NSX Edge Cluster

After the upgrade coordinator has been upgraded, based on your input, the upgrade coordinator updates the NSX Edge cluster, hosts, and the Management plane. Edge upgrade unit groups consist of NSX Edge nodes that are part of the same NSX Edge cluster. You can reorder Edge upgrade unit groups and enable or disable an Edge upgrade unit group from the upgrade sequence.

Note You cannot move an NSX Edge node from one Edge upgrade unit group to another because the Edge upgrade unit group membership adheres to the NSX Edge cluster membership before the upgrade.

The NSX Edge nodes are upgraded in serial mode so that when the upgrading node is down, the other nodes in the NSX Edge cluster remain active to continuously forward traffic.

The maximum limit of simultaneous upgrade of Edge upgrade unit groups is five.

Prerequisites

- Verify that the NSX Edge nodes are in an NSX Edge cluster.
- Familiarize yourself with the upgrade impact during and after the NSX Edge cluster upgrade. See [Operational Impact of the NSX-T Data Center Upgrade](#).

Procedure

- 1 Enter the NSX Edge cluster upgrade plan details.

| Option | Description |
|--|---|
| Serial | Upgrade all the Edge upgrade unit groups consecutively. This menu item is selected by default. This selection is applied to the overall upgrade sequence. |
| Parallel | Upgrade all the Edge upgrade unit groups simultaneously. For example, if the overall upgrade is set to the parallel order, the Edge upgrade unit groups are upgraded together and the NSX Edge nodes are upgraded one at a time. |
| When an upgrade unit fails to upgrade | Selected by default so that you can fix an error on the Edge node and continue the upgrade. You cannot deselect this setting. |
| After each group completes | Select to pause the upgrade process after each Edge upgrade unit group finishes upgrading. |

- 2 (Optional) Reorder the upgrade sequence of an Edge upgrade unit group.

For example, if you configure the overall group upgrade as serial, you can reorder the Edge upgrade unit groups serving internal networks or Edge upgrade unit groups interfacing with external networks to be upgraded first.

You cannot reorder the NSX Edge nodes within an Edge upgrade unit group.

- a Select the Edge upgrade unit group and click the **Actions** tab.
 - b Select **Reorder** from the drop-down menu.
 - c Select **Before** or **After** from the drop-down menu.
 - d Click **Save**.
- 3 (Optional) Disable an Edge upgrade unit group from the upgrade sequence.
You can disable some Edge upgrade unit groups and upgrade them later.
 - a Select the Edge upgrade unit group and click the **Actions** tab.
 - b Select **Change State > Disabled** to disable the Edge upgrade unit group.
 - c Click **Save**.
 - 4 (Optional) Click **Reset** to revert to the default state.

Caution After reset, you cannot restore your previous configuration.

- 5 Click **Start** to upgrade the NSX Edge cluster.

- 6 Monitor the upgrade process.

You can view the overall upgrade status and progress details of each Edge upgrade unit group. The upgrade duration depends on the number of Edge upgrade unit groups you have in your environment.

You can pause the upgrade to configure the Edge upgrade unit group that is not upgraded and restart the upgrade.

- 7 Click **Run Post Checks** to verify whether the Edge upgrade unit groups were successfully upgraded.

If some Edge upgrade unit groups failed to upgrade, resolve the errors.

- 8 (Optional) In the NSX Manager, select **System > Overview** and verify that the product version is updated on each NSX Edge node.

What to do next

If the process is successful, you can proceed with the upgrade. See [Configuring and Upgrading Hosts](#).

If there are upgrade errors, you must resolve the errors. See [Chapter 6 Troubleshooting Upgrade Failures](#).

Configuring and Upgrading Hosts

You can upgrade your hosts using the upgrade coordinator.

Configure Hosts

You can customize the upgrade sequence of the hosts, disable certain hosts from the upgrade, or pause the upgrade at various stages of the upgrade process.

All the existing standalone ESXi hosts, vCenter Server managed ESXi hosts, KVM hosts, and bare metal server are grouped in separate host upgrade unit groups by default.

Before you upgrade the hosts, you can select to update the hosts in parallel or serial mode. The maximum limit for a simultaneous upgrade is five host upgrade unit groups and ten hosts per group. When using APIs, make the calls on the orchestrator node.

Note Host upgrade unit group with hosts that belong to the same vCenter Server cluster can be upgraded serially.

You can customize the host upgrade sequence before the upgrade. You can edit a host upgrade unit group to move a host to a different host upgrade unit group that upgrades immediately and another host to a host upgrade unit group that upgrades later. If you have a frequently used host, you can reorder the host upgrade sequence within a host upgrade unit group so it is upgraded first and move the least used host to upgrade last.

Note You can upgrade your bare metal server using the same steps as provided for upgrading a KVM host.

Prerequisites

- If the ESXi hosts are part of a disabled DRS cluster or are standalone hosts, verify that they are placed in maintenance mode.

For ESXi hosts that are part of a fully automated DRS cluster, if the host is not in maintenance mode, the upgrade coordinator requests the host to be put in maintenance mode. vSphere DRS migrates the VMs to another host in the same cluster during the upgrade and places the host in maintenance mode.

- For ESXi host, for an in-place upgrade you do not need to power off the tenant VMs.
- For a KVM host, for an in-place upgrade you do not need to power off the VMs. For a maintenance mode upgrade, power off the VMs.
- Verify that the transport zone or transport node N-VDS name does not contain spaces.

If there are spaces, create a transport zone with no spaces in the N-VDS name. You must reconfigure all the components that are associated with the old transport zone to use the new transport zone and delete the old transport zone.

- Verify that your vSAN environment is in good health before you use the in-place upgrade mode.

See the *Place a Host in Maintenance Mode* section of the *vSphere Resource Management* guide.

Procedure

- 1 Enter the host upgrade plan details.

You can configure the overall group upgrade order to set the host upgrade unit groups to be upgraded first.

| Option | Description |
|--|--|
| Serial | Upgrade all the host upgrade unit groups consecutively. This menu item is selected by default and applied to the overall upgrade sequence. This selection is useful to maintain the step-by-step upgrade of the host components. For example, if the overall upgrade is set to serial and the host upgrade unit group upgrade is set to parallel, the host upgrade unit group is upgraded one after the other. The hosts within the group are updated in parallel. |
| Parallel | Upgrade all the host upgrade unit groups simultaneously. You can upgrade up to five hosts simultaneously. |
| When an upgrade unit fails to upgrade | Select to pause the upgrade process if any host upgrade fails. This selection allows you to fix the error on the host upgrade unit group and resume the upgrade. |
| After each group completes | Select to pause the upgrade process after each host upgrade unit group finishes upgrading. |

2 (Optional) Change the host upgrade unit group upgrade order.

If you configure the overall group upgrade in the serial order, the upgrade waits for a host upgrade unit group upgrade to finish before proceeding to upgrade the second host upgrade unit group. You can reorder the host upgrade unit group upgrade sequence to set a host upgrade unit group to upgrade first.

- a Select the host upgrade unit group and click the **Actions** tab.
- b Select **Reorder** from the drop-down menu.
- c Select **Before** or **After** from the drop-down menu.

3 (Optional) Remove a host upgrade unit group from the upgrade sequence.

- a Select the host upgrade unit group and click the **Actions** tab.
- b Select **Change State** from the drop-down menu.
- c Select **Disabled** to remove the host upgrade unit group.

4 (Optional) Change the individual host upgrade unit group upgrade sequence.

By default, the upgrade sequence is set to the parallel order.

- a Select the host upgrade unit group and click the **Actions** tab.
- b Select **Change Upgrade Order** from the drop-down menu.
- c Select **Serial** to change the upgrade sequence.

5 (Optional) Change the host upgrade unit group upgrade mode.

- Select **Maintenance** mode.

For standalone ESXi hosts and ESXi hosts that are part of a disabled DRS cluster, place the hosts into maintenance mode.

For KVM hosts, power off the VMs.

For ESXi hosts that are part of a fully automated DRS cluster, if the host is not in maintenance mode, the upgrade coordinator requests the host to be put in maintenance mode. vSphere DRS migrates the VMs to another host in the same cluster during the upgrade and places the host in maintenance mode.

- Select **In-place** mode to avoid powering off and placing a host into maintenance mode before the upgrade.

For standalone ESXi hosts and ESXi hosts that are part of a disabled DRS cluster, you do not need to place the hosts into maintenance mode.

For KVM hosts, you do not need to power off the VMs.

For ESXi hosts that are part of a fully automated DRS cluster, you do not need to place the host into maintenance mode.

Note During upgrade the host might experience a packet drop in the workload traffic.

- Use an API call `PUT https://<nsx-manager>/api/v1/upgrade/upgrade-unit-groups/<group-id>` and enable the upgrade coordinator to restart the ESXi host.

The `rebootless_upgrade:true` parameter states that after the ESXi host upgrade, the host is not rebooted.

By default, the upgrade coordinator does not restart the ESXi host. This mode is used for troubleshooting purposes.

- Use an API call `PUT https://<nsx-manager>/api/v1/upgrade/upgrade-unit-groups/<group-id>` and upgrade vCenter Server managed ESXi hosts that are part of a DRS cluster with vSAN configured.

The `ensure_object_accessibility` parameter requires vSAN to assume control of data accessibility while a vCenter Server managed ESXi host that is part of a DRS cluster is placed in maintenance mode for the upgrade.

The `evacuate_all_data` parameter requires vSAN to take all the data from a vCenter Server managed ESXi host that is part of a DRS cluster to another managed ESXi host that is part of a DRS cluster while placed in maintenance mode for the upgrade.

The `no_action` parameter requires vSAN to take no action while the vCenter Server managed ESXi host that is part of a DRS cluster is placed in maintenance mode for the upgrade.

For more information about the parameters, see the *Update the upgrade unit group* section of the *NSX-T Data Center REST API guide*.

- 6 Starting NSX-T Data Center 3.1.1, for vSphere Lifecycle Manager-enabled clusters, select one of the following options:
 - **NSX only Upgrade:** Use this option if you want to upgrade only NSX-T Data Center. The Upgrade Coordinator runs the entire upgrade process including the remediation of hosts.
 - **Stage in vSphere Lifecycle Manager:** Use this option if you want to upgrade NSX-T Data Center along with ESXi hosts and other solutions. You need to remediate the hosts using vSphere Lifecycle Manager. After remediation, you can monitor the upgrade from the Upgrade Coordinator.

- 7 Click **Reset** to discard your custom upgrade plan and revert to the default state.

Caution You cannot restore your previous upgrade configuration.

If you register a new host transport node during the upgrade, you must click **Reset** to view the status of the recently added host and to continue the upgrade process.

What to do next

Determine whether to add, edit, or delete host upgrade unit groups or to upgrade host upgrade unit groups. See [Manage Host Upgrade Unit Groups](#) or [Upgrade Hosts](#).

Manage Host Upgrade Unit Groups

You can edit and delete an existing host upgrade unit group before you start the upgrade or after you pause the upgrade.

Hosts in a ESXi cluster appear in one host upgrade unit group in the upgrade coordinator. You can move these hosts from one host upgrade unit group to another host upgrade unit group.

Note If any of the hosts are part of a vSAN enabled cluster, retain the default upgrade unit groups without recreating any groups.

Prerequisites

- Verify that you have configured the overall hosts upgrade. See [Configure Hosts](#).
- If the ESXi hosts are part of a disabled DRS cluster or are standalone hosts, verify that they are placed in maintenance mode.

For ESXi hosts that are part of a fully automated DRS cluster, if the host is not in maintenance mode, the upgrade coordinator requests the host to be put in maintenance mode. vSphere DRS migrates the VMs to another host in the same cluster during the upgrade and places the host in maintenance mode.

- For ESXi host, for an in-place upgrade you do not need to power off the tenant VMs.
- For a KVM host, for an in-place upgrade you do not need to power off the VMs. For a maintenance mode upgrade, power off the VMs.

Procedure

- 1 Create a host upgrade unit group.
 - a Click **Add** to include existing hosts into a host upgrade unit group.
 - b Toggle the **State** button to enable or disable the host upgrade unit group from the upgrade.
 - c Select an existing host and click the arrow icon to move that host to the newly created host upgrade unit group.

If you select an existing host that was part of a host upgrade unit group, the host is moved to the new host upgrade unit group.
 - d Select whether to upgrade the host upgrade unit group in parallel or serial mode.
 - e Select the upgrade mode.

See step 5 of [Configure Hosts](#).
 - f (Optional) Select **Reorder** from the drop-down menu to reposition the host upgrade unit groups.
 - g (Optional) Select **Before** or **After** from the drop-down menu.

2 Move an existing host to another host upgrade unit group.

If an enabled DRS ESXi cluster is part of the upgrade, then a host upgrade unit group is created for the hosts managed by this cluster.

- a Select a host upgrade unit group.
- b Select a host.
- c Click the **Actions** tab.
- d Select **Change Group** from the drop-down menu to move the host to another host upgrade unit group.
- e Select the host upgrade unit group name from the drop-down menu to move the host to.
- f (Optional) Select **Reorder** from the drop-down menu to reposition the host within the host upgrade unit group.
- g (Optional) Select **Before** or **After** from the drop-down menu.

3 Delete a host upgrade unit group.

You cannot delete a host upgrade unit group that has hosts. You must first move the hosts to another group.

- a Select the host upgrade unit group.
- b Select a host.
- c Click the **Actions** tab.
- d Select **Change Group** from the drop-down menu to move the host to another host upgrade unit group.
- e Select the host upgrade unit group name from the drop-down menu to move the host to.
- f Select the host upgrade unit group you want to remove and click **Delete**.
- g Accept the notification.

What to do next

Upgrade the newly configured hosts. See [Upgrade Hosts](#).

Upgrade Hosts

Upgrade the hosts in your environment using the upgrade coordinator.

Prerequisites

- Verify that you have configured the overall hosts upgrade plan. See [Configure Hosts](#).
- If the ESXi hosts are part of a disabled DRS cluster or are standalone hosts, verify that they are placed in maintenance mode.

For ESXi hosts that are part of a fully automated DRS cluster, if the host is not in maintenance mode, the upgrade coordinator requests the host to be put in maintenance mode. vSphere DRS migrates the VMs to another host in the same cluster during the upgrade and places the host in maintenance mode.

- For ESXi host, for an in-place upgrade you do not need to power off the tenant VMs.
- For a KVM host, for an in-place upgrade you do not need to power off the VMs. For a maintenance mode upgrade, power off the VMs.
- For a stateless ESXi host, log in vCenter Server and update the ESXi image with the NSX-T Data Center kernel modules.

Procedure

- 1 Click **Start** to upgrade the hosts.

For vSphere Lifecycle Manager-enabled clusters, see [Upgrade a vSphere Lifecycle Manager-enabled Cluster](#).

- 2 Click **Refresh** and monitor the upgrade process.

You can view the overall upgrade status and specific progress of each host upgrade unit group. The upgrade duration depends on the number of host upgrade unit groups you have in your environment.

Wait until the in progress upgrade units are successfully upgraded. You can then pause the upgrade to configure the host upgrade unit group that is not upgraded and resume the upgrade.

- 3 Click **Run Post Checks** to make sure that the upgraded hosts and NSX-T Data Center do not have any problems.

Note If a host upgrade unit failed to upgrade and you removed the host from NSX-T Data Center, refresh the upgrade coordinator to view all the successfully upgraded host upgrade units.

If a host fails during the upgrade, reboot the host and try the upgrade again.

- 4 After the upgrade is successful, verify that the latest version of NSX-T Data Center packages is installed on the vSphere, KVM hosts, and bare metal server.

- For vSphere hosts, enter `esxcli software vib list | grep nsx`
- For Ubuntu hosts, enter `dpkg -l | grep nsx`
- For SUSE Linux Enterprise Server, Red Hat, or CentOS hosts, enter `rpm -qa | egrep 'nsx|openvswitch|nicira'`

- 5 Power on the tenant VMs of standalone ESXi hosts that were powered off before the upgrade.
- 6 Migrate the tenant VMs on hosts managed by vCenter Server that are part of the enabled DRS cluster to the appropriate host.

- 7 Power on or return the tenant VMs of ESXi hosts that are part of a disabled DRS cluster that were powered off before the upgrade.

What to do next

You can proceed with the upgrade only after the upgrade process finishes successfully. If some of the hosts are disabled, you must enable and upgrade them before you proceed. See [Upgrade Management Plane](#).

If there are upgrade errors, you must resolve the errors. See [Chapter 6 Troubleshooting Upgrade Failures](#).

Upgrade a vSphere Lifecycle Manager-enabled Cluster

Starting NSX-T Data Center 3.1.1 you can upgrade the clusters that have vSphere Lifecycle Manager enabled.

Prerequisites

Verify that you have configured the overall hosts upgrade plan. See [Configure Hosts](#).

Procedure

- 1 For clusters set up as **Stage in vSphere Lifecycle Manager**, click **Stage** to copy the NSX vib to vSphere Lifecycle Manager and to update the cluster with the new NSX image. Also stage the vib for the solutions that you are upgrading along with NSX-T Data Center.
- 2 Click **Start** to upgrade the hosts.
- 3 For clusters set up as **Stage in vSphere Lifecycle Manager**, log in the vCenter Server and remediate the hosts.

For clusters set up as **NSX only Upgrade**, the Upgrade Coordinator performs the entire upgrade process including the remediation of hosts.

- 4 Click **Refresh** and monitor the upgrade process from NSX Manager.

You can view the overall upgrade status and specific progress of each host upgrade unit group. The upgrade duration depends on the number of host upgrade unit groups you have in your environment.

Wait until the in progress upgrade units are successfully upgraded. You can then pause the upgrade to configure the host upgrade unit group that is not upgraded and resume the upgrade.

- 5 Click **Run Post Checks** to make sure that the upgraded hosts and NSX-T Data Center do not have any problems.

Note If a host upgrade unit failed to upgrade and you removed the host from NSX-T Data Center, refresh the upgrade coordinator to view all the successfully upgraded host upgrade units.

If a host fails during the upgrade, reboot the host and try the upgrade again.

- 6 After the upgrade is successful, verify that the latest version of NSX-T Data Center packages is installed.

```
esxcli software vib list | grep nsx
```

What to do next

You can proceed with the upgrade only after the upgrade process finishes successfully. If some of the hosts are disabled, you must enable and upgrade them before you proceed. See [Upgrade Management Plane](#).

If there are upgrade errors, you must resolve the errors. See [Chapter 6 Troubleshooting Upgrade Failures](#).

Upgrade Hosts Manually

You can manually upgrade hosts in a host upgrade unit group.

Prerequisites

Verify that the upgrade coordinator is updated. See [Upgrade the Upgrade Coordinator](#).

Procedure

- 1 In the upgrade coordinator, navigate to the Host Upgrade tab.
- 2 Click **Stage** and proceed after staging is complete.
- 3 Upgrade your ESXi host manually.

Note If a host fails during the upgrade, reboot the host and try the upgrade again.

- a Put the ESXi host in Maintenance mode.
- b Navigate to the ESXi offline bundle location from the NSX Manager.

```
http://<nsx-manager-ip-address>:8080/repository/<target-nsx-t-version>/metadata/manifest.
```
- c Download the ESXi offline bundle to /tmp on ESXi.
- d Upgrade the ESXi host.

```
esxcli software vib install -d /tmp/<offline-bundle-name>.
```

4 Upgrade your KVM host manually.

Note If a host fails during the upgrade, reboot the host and try the upgrade again.

- a Download the upgrade script.

```
http://<nsx-manager-ip-address>:8080/repository/<target-nsx-t-version>/
HostComponents/<os-type>/upgrade.sh
```

Where the `os_type` is `rhel76_x86_64`, `rhel77_x86_64`, `xenial_amd64`, `linux64-bionic`, `linux64-sles12sp3`, or `linux64-sles12sp4`.

- b Upgrade the KVM host.

```
upgrade.sh <host-upgrade-bundle-url> <checksum>
```

Where the host upgrade bundle URL is, `http://<nsx-manager-ip-address>:8080/xyz` where `xyz`, is one of the paths from the `http://<nsx-manager-ip-address>:8080/repository/<target-nsx-version>/metadata/manifest` file.

For example, `http://<nsx-manager-ip-address>:8080/repository/3.0.0.0.99999999/HostComponents/rhel76_x86_64/nsx-lcp-2.3.0.0.99999999-rhel76_x86_64.tar.gz`.

To retrieve `checksum`, log in to NSX Manager as a root user and run the following command:

```
sha256sum /repository/<target-nsx-version>/HostComponents/<os-type>/*
```

- 5 In the upgrade coordinator, navigate to the **Hosts** tab and refresh the page.

All the manually upgraded hosts appear in the upgraded state.

- 6 After the upgrade is successful, verify that the latest version of NSX-T Data Center packages is installed on the vSphere and KVM hosts.

- For vSphere hosts, enter `esxcli software vib list | grep nsx`.
- For Ubuntu hosts, enter `dpkg -l | grep nsx`.
- For SUSE Linux Enterprise Server, Red Hat, or CentOS hosts, enter `rpm -qa | egrep 'nsx|openvswitch|nicira'`.

- 7 Power on the tenant VMs of standalone ESXi hosts that were powered off before the upgrade.

- 8 Migrate the tenant VMs of managed ESXi hosts that are part of the DRS disabled cluster to the appropriate host.

- 9 Power on or return the tenant VMs of ESXi hosts that are part of a DRS disabled cluster that were powered off before the upgrade.

- 10 (Optional) In the NSX Manager appliance, select **System > Appliances** and verify that all the status indicators for host and transport node deployment appear as installed and connection status is up and green.

- 11 In the upgrade coordinator, navigate to the **Hosts** tab and select a disabled host upgrade unit group.
- 12 Select **Actions > Change State > Enabled**.

If you have other disabled host upgrade unit groups, set them to **Enabled**.

What to do next

You can proceed with the upgrade only after the upgrade process finishes successfully. See [Upgrade Management Plane](#).

If there are upgrade errors, you must resolve the errors. See [Chapter 6 Troubleshooting Upgrade Failures](#).

Upgrade Management Plane

The upgrade sequence upgrades the Management Plane at the end. When the Management Plane upgrade is in progress, avoid any configuration changes from any of the nodes.

Note After you initiate the upgrade, the NSX Manager user interface is briefly inaccessible.

Prerequisites

Verify that the NSX Edge cluster is upgraded successfully. See [Upgrade NSX Edge Cluster](#).

Procedure

- 1 Backup the NSX Manager.

See the *NSX-T Data Center Administration Guide*.

- 2 Click **Start** to upgrade the Management plane.
- 3 Accept the upgrade notification.

You can safely ignore any upgrade related errors such as, HTTP service disruption that appears at this time. These errors appear because the Management plane is rebooting during the upgrading.

- 4 Monitor the upgrade progress from the NSX Manager CLI for the orchestrator node. The NSX Manager user interface might be inaccessible.

```
get upgrade progress-status
```

Note Do not reboot the appliance while the upgrade is in progress. It might take several minutes for all the nodes to be upgraded and for the cluster to reach a stable state.

You can log in to the NSX Manager user interface when `get upgrade progress-status` indicates that the upgrade is successful and the NSX Manager services have started.

- 5 In the CLI, log in to the NSX Manager to check the cluster status and verify that the services have started.

- `get service`

When the services start, the Service state appears as running. Some of the services include, SSH, install-upgrade, and manager.

`get service` lists the IP address of the orchestrator node. See `Enabled on`. Use this IP address throughout the upgrade process.

Note Ensure that you do not use any type of Virtual IP address to upgrade NSX-T Data Center.

If the services are not running, troubleshoot the problem. See the *NSX-T Data Center Troubleshooting Guide*.

- `get cluster status`

If the group status is not Stable, troubleshoot the problem. See the *NSX-T Data Center Troubleshooting Guide*.

What to do next

Perform post-upgrade tasks or troubleshoot errors depending on the upgrade status. See [Chapter 5 Post-Upgrade Tasks](#) or [Chapter 6 Troubleshooting Upgrade Failures](#).

Upgrading NSX Cloud Components

4

NSX Cloud components are upgraded using the following workflow.

Upgrading NSX Cloud components from 3.2.x to 4.0.x

If you are upgrading NSX Cloud components from NSX-T Data Center 3.2.x to 4.0.x, follow this checklist:

| Task | Instructions |
|---|---|
| <input type="checkbox"/> Run the day-0 NSX Cloud scripts to update permissions for the PCG role in your public cloud. | See Regenerate the Public Cloud Permissions |
| <input type="checkbox"/> Upgrade the Upgrade Coordinator from CSM. | See Upgrade the Upgrade Coordinator from CSM . |
| <input type="checkbox"/> Upgrade the Upgrade Coordinator from NSX Manager. | See: Upgrade the Upgrade Coordinator from NSX Manager . |
| <input type="checkbox"/> Upgrade the NSX Tools first followed by the PCG upgrade. | See Upgrade NSX Tools and PCG . |
| <input type="checkbox"/> Upgrade CSM. | See Upgrade CSM |
| <input type="checkbox"/> Upgrade NSX Manager. | See Upgrade NSX Manager . |

Procedure

1 [Regenerate the Public Cloud Permissions](#)

Before upgrading NSX Cloud components, regenerate the necessary permissions for your public cloud account required by NSX Cloud.

2 [Upgrade the Upgrade Coordinator from CSM](#)

Follow these instructions to first download the upgrade bundle in CSM and then upgrade the Upgrade Coordinator from CSM

3 [Upgrade the **Upgrade Coordinator** from NSX Manager](#)

Follow these instructions to download the upgrade bundle in NSX Manager and upgrade the **Upgrade Coordinator** from NSX Manager.

4 [Upgrade NSX Tools and PCG](#)

You must first upgrade NSX Tools and then PCG.

5 Upgrade NSX Manager

Follow these instructions to upgrade NSX Manager.

6 Upgrade CSM

In the current release, CSM can only be upgraded using NSX CLI.

Regenerate the Public Cloud Permissions

Before upgrading NSX Cloud components, regenerate the necessary permissions for your public cloud account required by NSX Cloud.

- Microsoft Azure: See: *Generate the Service Principal and Roles* in the *NSX-T Data Center Installation Guide*.
- AWS: See: *Generate the IAM Profile and PCG Role* in the *NSX-T Data Center Installation Guide*.

Upgrade the Upgrade Coordinator from CSM

Follow these instructions to first download the upgrade bundle in CSM and then upgrade the Upgrade Coordinator from CSM

Download the NSX Cloud Upgrade Bundle

Begin the upgrade process by downloading the NSX Cloud upgrade bundle.

The NSX Cloud upgrade bundle contains all the files to upgrade the NSX Cloud infrastructure. Before you begin the upgrade process, you must download the correct upgrade bundle version.

Procedure

- 1 In the VMware download portal, locate the NSX-T Data Center version available to upgrade and navigate to **Product Downloads > NSX Cloud Upgrade Bundle for NSX-T <version>**.
- 2 Verify that the main upgrade bundle (.mub) filename has a format similar to `VMware-CC-upgrade-bundle-ReleaseNumberNSXBuildNumber.mub`.

Note This is a separate file and must be downloaded in addition to the NSX-T Data Center upgrade bundle.

- 3 Click **Download Now** to download the NSX Cloud upgrade bundle.

Note The upgrade bundle is uploaded into CSM. Download it either on the same system from where you access the CSM UI, or note the location of the system where you download it, to provide a remote URL of this system into CSM for uploading.

What to do next

[Upgrade the Upgrade Coordinator in CSM.](#)

Upgrade the Upgrade Coordinator in CSM

Upload the upgrade bundle and upgrade the Upgrade Coordinator appliance in CSM

Procedure

- 1 Log in to CSM with the Enterprise Administrator role.
- 2 Click **Utilities > Upgrade**
- 3 Click **Upload Upgrade Bundle**. Pick a location for the upgrade bundle. You can provide a remote location using a URL.
- 4 After the upgrade bundle finishes uploading in CSM, click **Prepare for Upgrade** to start the process of upgrading the Upgrade Coordinator.

Note: The upgrade bundle must be a valid file in the .nub format. Do not use .nub or other files. See [Upgrade the Upgrade Coordinator](#) for details.

When the Upgrade Coordinator upgrade process finishes, the **Begin Upgrade** button becomes active.

What to do next

[Upgrade the Upgrade Coordinator from NSX Manager](#) .

Upgrade the Upgrade Coordinator from NSX Manager

Follow these instructions to download the upgrade bundle in NSX Manager and upgrade the **Upgrade Coordinator** from NSX Manager.

- Download the upgrade bundle: [Download the NSX-T Data Center Upgrade Bundle](#)
- Upgrade the Upgrade Coordinator from NSX Manager: [Upgrade the Upgrade Coordinator](#)

What to do next

[Upgrade NSX Tools and PCG](#)

Upgrade NSX Tools and PCG

You must first upgrade NSX Tools and then PCG.

Prerequisites

- Outbound port 8080 must be open on workload VMs that need to be upgraded.
- The PCGs must be powered on when the upgrade of NSX Tools installed on workload VMs or of PCGs is in progress.

Procedure

- 1 Log in to CSM with the Enterprise Administrator role.

- 2 Click **Utilities > Upgrade > Begin Upgrade**. The **Upgrade CSM** wizard starts.

Note: Although the name of the wizard is **Upgrade CSM**, you can only upgrade NSX Tools and PCG from this wizard.

- 3 In the **Upgrade CSM > Overview** screen, you can see an overview of the default upgrade plan. Based on the upgrade bundle you have uploaded, you can see which versions of NSX Tools and PCG are compatible for an upgrade via the upgrade bundle uploaded.
- 4 Click **Next**. The **CSM > Select NSX Tools** screen appears.

A list of all compatible NSX Tools that can be upgraded to the target version in all your VPCs or VNets, are displayed. You can filter NSX Tools based on which private cloud network they are in or which OS they are deployed on. All NSX-managed VMs are eligible for upgrade and listed for you to select. Fix any errors on NSX-managed VMs which are quarantined before selecting them for upgrade to prevent the upgrade of NSX Tools on such VMs from failing.

- 5 Select the NSX Tools you want to upgrade and move them to the **Selected** window.

Note When upgrading from 3.0.x or 3.1.x to 3.2.0 and later, make sure you first upgrade NSX Tools and then PCG. You might notice inter-VPC traffic loss on the VMs where PCG is upgraded to 3.2.0 or later but the NSX Tools are still not upgraded to 3.2.0 or later.

- 6 Click **Next**. CSM downloads the upgrade bits to the PCG on which the NSX Tools reside. The PCG copies these upgrade bits to the VMs which have been selected for upgrade.

If you have an HA pair of PCG, CSM downloads the upgrade bits to each PCG and starts upgrading the selected NSX Tools. NSX Tools in the same VPC/VNet are upgraded in parallel. Ten NSX Tools under a VPC/VNet are upgraded simultaneously.

If you have more than ten NSX Tools, they are queued for upgrading. PCG maintains a flag on VMs that are unreachable and attempts to upgrade them when they can be reached. For example, a powered off workload VM is upgraded when powered on again and able to communicate with PCG. Similarly for a workload VM on which port 8080 is blocked at first but when port 8080 is opened and PCG can access it, the upgrade for that workload VM proceeds. If some NSX Tools are not able to be upgraded, you can skip upgrading them in order to proceed. See [Skip Upgrading NSX Tools](#) for details on this option. If you run into problems while upgrading NSX Tools, refer to these troubleshooting instructions: [Troubleshooting NSX Tools Upgrade on Windows Workload VMs](#) and [Troubleshooting NSX Tools Upgrade on Linux Workload VMs](#).

- 7 Click **Next** to proceed with upgrading the PCG. With an HA pair of PCGs, there are two fail-overs during the upgrade process and when the upgrade finishes, the preferred PCG is reinstated as the active gateway.
- 8 Click **Finish**.

Results

PCGs and NSX Tools are upgraded.

Note If you are upgrading from NSX-T Data Center 2.x to NSX-T Data Center 3.x and you have service insertion set up in version 2.x, you must create a lowest priority default catch-all rule with the action set to **Do Not Redirect**. Follow instructions described in "Set Up Redirection Rules" in the *NSX-T Data Center Administration Guide*.

How long does the upgrade process take

Note CSM and NSX-T Data Center components are upgraded separately, and that time is not included here. This is an estimation to help you plan your upgrade cycles.

- **One or an HA pair of PCGs:** PCGs in different VPCs or VNets are upgraded in parallel, but PCGs in HA pair upgrade serially. It takes about 20 minutes for one PCG to upgrade.
- **One VPC or VNet:** For a VPC or VNet with up to 10 VMs and an HA pair of PCGs, it can take up to 45 minutes to upgrade. This time may vary depending on the OS on the VMs and their size.
- **NSX Tools installed on a workload VM:** It takes from 3 to 5 minutes for each NSX Tools installation on a VM to upgrade, not accounting for the time it takes to upload the upgrade bundle from CSM to the public cloud. 10 VMs with NSX Tools installed are upgraded simultaneously. For multiple compute VPCs/VNets per Transit VPC/VNet, all VMs with NSX Tools installed on one Compute VPC/VNet are first upgraded before proceeding to the next. The time to upgrade NSX Tools also varies for different operating systems and the VM size.

What to do next

Follow the next step in the checklist that applies to the version you are upgrading from: [Chapter 4 Upgrading NSX Cloud Components](#) .

Skip Upgrading NSX Tools

You can skip upgrading NSX Tools for reasons listed here.

Except under the following scenarios, do not skip the upgrade of NSX Tools because VMs with NSX Tools in a different version compared to PCG will lose connectivity with the PCG.

Scenarios for skipping NSX Tools upgrade:

- You are upgrading to 3.0.x or 3.1.x from an earlier version. In this case skip upgrading NSX Tools, upgrade PCG, and return to upgrading NSX Tools.
You are able to upgrade NSX Tools after the upgrade of PCG in this case because the system maintains connectivity for the duration of this upgrade.
- You want to upgrade only selected private clouds within your public cloud.
- You do not want any downtime on certain critical managed workload VMs.
- You do not want powered off VMs to block the upgrade process.

- You might want to apply a bug-fix patch only to the PCG without affecting NSX Tools.

Troubleshooting NSX Tools Upgrade on Windows Workload VMs

Upgrading NSX Tools on Windows workload VMs might fail at first. Try the following troubleshooting options.

Manually uninstall and reinstall NSX Tools

If NSX Tools are not getting upgraded, you might have to manually uninstall them, recover the system, and then install the new version. Follow these steps:

- 1 Uninstall NSX Tools by running the command:

```
> powershell -file nsx_install.ps1 -operation uninstall
```

- 2 Recover the system and restore it to a stable state by running the following commands:

- a Check whether any NSX or OVS services are still running:

```
> powershell Get-ScheduledTask -Taskname nsx_watchdog
> powershell Unregister-ScheduledTask -TaskName nsx_watchdog
> tasklist | findstr nsx
> tasklist | findstr ovs
```

- b If NSX/OVS services are running, stop the services in the following order:

```
> sc.exe stop nsx-agent
> sc.exe delete nsx-agent

> sc.exe stop nsx-exporter
> sc.exe delete nsx-exporter

> sc.exe stop nsx-vm-command-relay-agent
> sc.exe delete nsx-vm-command-relay-agent

> sc.exe stop ovs-vswitchd
> sc.exe delete ovs-vswitchd

> sc.exe stop ovsdb-server
> sc.exe delete ovs-vswitchd
```

- c Check whether the OVSIM kernel driver is installed. If installed, manually uninstall the driver.

```
>netcfg -q ovsim
>netcfg /u ovsim
```


- d Reset TCP/IP stack to restore the TCP/IP stack to default state.

```
> netsh winsock reset
> netsh int ip reset
```

- e Remove all NSX components files.

```
> Remove-Item "C:\ProgramData\VMware\NSX\Data" -Force
> Remove-Item "C:\Program Files\VMware\NSX" -Force
```

- f Reboot the system. After reboot, clean up the driver (INF) files. Retrieve the INF file name using `nsx_conf.json`.

Note If the file `nsx_conf.json` is not present, skip this step.

```
> C:\Windows\system32>more C:\ProgramData\VMware\NSX\Data\nsx_conf.json

{
  "NSX": {
    "version": null,
    "OVS": {
      "version": "2.12.1.32033",
      "driver_inf": "oem9.inf"
    }
  }
}

> pnputil -d oem9.inf
```

- 3 Install NSX Tools by following instructions at "Install NSX Tools" in the *NSX-T Data Center Administration Guide*.
- 4 In your public cloud, remove the `nsx.network=default` tag from the VM, wait for at least two minutes and add the tag back. This ensures the workload VM gets connected with the PCG.

Troubleshooting NSX Tools Upgrade on Linux Workload VMs

Upgrading NSX Tools on Linux workload VMs might fail at first.

From the Linux workload VMs where upgrade failed, uninstall NSX Tools and reinstall the new version of NSX Tools.

- 1 To uninstall NSX Tools:
 - a Remote log in to the VM using SSH.
 - b Run the installation script with the uninstall option: `sudo ./install_nsx_vm_agent.sh --uninstall`

- 2 To reinstall NSX Tools, see instructions in "Install NSX Tools on Linux VMs" in the *NSX-T Data Center Administration Guide*.
- 3 In your public cloud, remove the `nsx.network=default` tag from the VM, wait for at least two minutes and add the tag back. This ensures the workload VM gets connected with the PCG.

Upgrade NSX Manager

Follow these instructions to upgrade NSX Manager.

Note If you are upgrading from 2.5.0, upgrade NSX Manager after upgrading CSM.

See [Upgrade Management Plane](#).

What to do next

[Upgrade CSM](#).

Upgrade CSM

In the current release, CSM can only be upgraded using NSX CLI.

Prerequisites

- See [Chapter 4 Upgrading NSX Cloud Components](#) to find the correct order to follow for upgrading CSM.
- You must have extracted the file `VMware-NSX-unified-appliance-<version>.nub` from the NSX Cloud main upgrade bundle (MUB) and hosted on an FTP server accessible from CSM.

Procedure

- 1 Log in to NSX CLI with CSM admin credentials:

```
$ssh <csm-admin>@<NSX-CSM-IP>
```

and run the following NSX CLI command:

```
nsxcsm> copy url scp://<username>@<ftp-server-ip>/<path-to-file>/VMware-NSX-unified-appliance-<version>.nub
```

- 2 Extract and verify the file `VMware-NSX-unified-appliance-<version>.nub`:

```
nsxcsm> verify upgrade-bundle VMware-NSX-unified-appliance-<version>
```

Example output:

```

Checking upgrade bundle /var/vmware/nsx/file-store/VMware-NSX-unified-appliance-
<version>.nub contents
Verifying bundle VMware-NSX-unified-appliance-<version>.bundle with signature VMware-NSX-
unified-appliance-<version>.bundle.sig
Moving bundle to /image/VMware-NSX-unified-appliance-<version>.bundle
Extracting bundle payload
Successfully verified upgrade bundle
Bundle manifest:
  appliance_type: 'nsx-unified-appliance'
  version: '<upgrade version>'
  os_image_path: 'files/nsx-root.fsa'
  os_image_md5_path: 'files/nsx-root.fsa.md5'
Current upgrade info:
{
  "info": "",
  "body": {
    "meta": {
      "from_version": "<current version>",
      "old_config_dev": "/dev/mapper/nsx-config",
      "to_version": "<post-upgrade version>",
      "new_config_dev": "/dev/mapper/nsx-config__bak",
      "old_os_dev": "/dev/xvda2",
      "bundle_path": "/image/VMware-NSX-unified-appliance-<version>",
      "new_os_dev": "/dev/xvda3"
    },
    "history": []
  },
  "state": 1,
  "state_text": "CMD_SUCCESS"
}

```

3 Start the upgrade:

```

nsxscsm> start upgrade-bundle VMware-NSX-unified-appliance-<version> playbook VMware-NSX-
cloud-service-manager-<version>-playbook

```

Example output:

```

Validating playbook /var/vmware/nsx/file-store/VMware-NSX-cloud-service-manager-<version>-
playbook.yml
Running "shutdown_csm_svc" (step 1 of 6)
Running "install_os" (step 2 of 6)
Running "migrate_csm_config" (step 3 of 6)

System will now reboot (step 4 of 6)
After the system reboots, use "resume" to start the next step, "start_csm_svc".
{
  "info": "",
  "body": null,
  "state": 1,
  "state_text": "CMD_SUCCESS"
}

```

```
}
Autoimport-nsx-cloud-service-manager-thin>
Broadcast message from root@Autoimport-nsx-cloud-service-manager-thin (Fri 2017-08-25
21:11:36 UTC):

The system is going down for reboot at Fri 2017-08-25 21:12:36 UTC!
```

- 4 Wait for the upgrade to complete. CSM reboots during upgrade, and the upgrade is finalized when the CSM UI restarts after rebooting.
- 5 Verify the version of CSM to confirm that it has upgraded:

```
nsxcsn> get version
```

Results

The CSM appliance is upgraded and the PCGs are automatically resized to 191 GB.

What to do next

- If you are upgrading from 3.0.x to later, follow the [Chapter 5 Post-Upgrade Tasks](#) steps as you have already upgraded NSX-T Data Center.
- If you are upgrading from version 2.5.0 to later, proceed to [Chapter 3 Upgrading NSX-T Data Center](#).

Post-Upgrade Tasks

5

After you upgrade NSX-T Data Center, perform post-upgrade verification tasks to check whether the upgrade was successful.

Read the following topics next:

- [Verify the Upgrade](#)

Verify the Upgrade

After you upgrade NSX-T Data Center, you can verify whether the versions of the upgraded components have been updated. For more information on the NSX Manager, see "Overview of the NSX Manager" in the *NSX-T Data Center Administration Guide*.

Prerequisites

Perform a successful upgrade. See [Chapter 3 Upgrading NSX-T Data Center](#).

Procedure

- 1 From your browser, log in as a local admin user to an NSX Manager at `https://nsx-manager-ip-address/login.jsp?local=true`.
- 2 Select **System > Upgrade**.

- 3 Verify that the overall upgrade version, component version, and initial and target product version are accurate.
 - a (Optional) Verify that the Dashboard, fabric hosts, NSX Edge cluster, transport nodes, and all logical entities status indicators are green, normal, deployed, and do not show any warnings.
 - b (Optional) Verify the status of several components.
 - Fabric nodes installation
 - Transport node Local Control Plane (LCP) and Management plane agent connectivity
 - Routers connectivity
 - NAT rules
 - DFW rules
 - DHCP lease
 - BGP details
 - Flows in the IPFIX collector
 - TOR connectivity to enable the network traffic

The status of the upgrade appears as Successful.

- 4 Modify the default admin password expiration.

If the password expires, you will be unable to log in and manage components. Additionally, any task or API call that requires the administrative password to execute will fail. By default, passwords expire after 90 days. If your password expires, see Knowledge Base article 70691 [NSX-T admin password expired](#).

- a Reset the expiration period.

You can set the expiration period for between 1 and 9999 days.

```
nsxcli set user admin password-expiration <1 - 9999>
```

- b (Optional) You can disable password expiry so the password never expires.

```
nsxcli clear user admin password-expiration
```

- 5 If you have an existing Ubuntu KVM host as a transport node, back up the `/etc/network/interfaces` file.
- 6 If you have VIDM enabled, access your the local account at `https://nsx-manager-ip-address/login.jsp?local=true`.
- 7 Verify CPU and Memory values for NSX Edge VMs.

After upgrading, log in to the vSphere Client to verify if your existing NSX Edge VMs are configured with the following CPU and Memory values. If they are not, edit the VM settings to match these values.

| NSX-T Data Center Appliance | Memory | vCPU |
|------------------------------------|---------------|-------------|
| NSX Edge Small VM | 4 GB | 2 |
| NSX Edge Medium VM | 8 GB | 4 |
| NSX Edge Large VM | 32 GB | 8 |

Troubleshooting Upgrade Failures

6

You can review the support bundle log messages to identify the upgrade problem.

You can also perform any of the following debugging tasks.

- Log in to the NSX Manager CLI as root user and navigate to the upgrade coordinator log files `/var/log/upgrade-coordinator/upgrade-coordinator.log`.
- Navigate to the system log files `/var/log/syslog` or API log files `/var/log/proton/nsxapi.log`.
- Configure a remote logging server and send log messages for troubleshooting. See *NSX-T Data Center Administration Guide*.

Note If you are unable to troubleshoot the failure and want to revert to the previous working version of NSX-T Data Center, contact VMware support.

Read the following topics next:

- [Collect Support Bundles](#)
- [Upgrade Fails Due to a Timeout](#)
- [Upgrade Fails Due to Insufficient Space in Bootbank on ESXi Host](#)
- [Unable to Upgrade Host Placed in NSX Maintenance Mode](#)
- [Failure to Upload the Upgrade Bundle](#)
- [Backup and Restore During Upgrade](#)
- [Loss of Controller Connectivity after Host Upgrade](#)
- [In-place Upgrade Fails](#)
- [Upgrade Coordinator User Interface is Inaccessible](#)
- [NSX Manager User Interface is Inaccessible During Upgrade](#)

Collect Support Bundles

You can collect support bundles on registered cluster and fabric nodes and download the bundles to your machine or upload them to a file server.

If you choose to download the bundles to your machine, you get a single archive file consisting of a manifest file and support bundles for each node. If you choose to upload the bundles to a file server, the manifest file and the individual bundles are uploaded to the file server separately.

NSX Cloud Note If you want to collect the support bundle for CSM, log in to CSM, go to **System > Utilities > Support Bundle** and click **Download**. The support bundle for PCG is available from NSX Manager using the following instructions. The support bundle for PCG also contains logs for all the workload VMs.

If you want to collect support bundles for Antrea container clusters that are registered to NSX-T Data Center, see *Collect Support Bundles for an Antrea Container Cluster* in the *NSX-T Data Center Administration Guide*.

NSX Application Platform Note For information about collecting support bundles for NSX Application Platform, see the *Deploying and Managing the VMware NSX Application Platform* documentation.

Procedure

1 From your browser, log in as a local admin user to an NSX Manager at `https://nsx-manager-ip-address/login.jsp?local=true`.

2 Select **System > Support Bundle**

3 Select the target nodes.

The available types of nodes are **Management Nodes, Edges, Hosts, and Public Cloud Gateways**.

4 (Optional) Specify log age in days to exclude logs that are older than the specified number of days.

5 (Optional) Toggle the switch that indicates whether to include or exclude core files and audit logs.

Note Core files and audit logs might contain sensitive information such as passwords or encryption keys.

6 (Optional) Select the check box to upload the bundles to a remote file server.

7 Click **Start Bundle Collection** to start collecting support bundles.

Depending on how many log files exist, each node might take several minutes.

8 Monitor the status of the collection process.

The status tab shows the progress of collecting support bundles.

- 9 Click **Download** to download the bundle if the option to send the bundle to a file remote server was not set.

The bundle collection may fail for a manager node if there is not enough disk space. If you encounter an error, check whether older support bundles are present on the failed node. Log in to the NSX Manager UI of the failed manager node using its IP address and initiate the bundle collection from that node. When prompted by the NSX Manager, either download the older bundle or delete it.

Upgrade Fails Due to a Timeout

An event during the upgrade process fails and the message from the Upgrade Coordinator indicates a timeout error.

Problem

During the upgrade process, the following events might fail because they do not complete within a specific time. The Upgrade Coordinator reports a timeout error for the event and the upgrade fails.

| Event | Timeout Value |
|---|---------------|
| Putting a host into maintenance mode | 4 hours |
| Waiting for a host to reboot | 32 minutes |
| Waiting for the NSX service to be running on a host | 13 minutes |

Solution

- ◆ For the maintenance mode issue, log in to vCenter Server and verify the status of tasks related to the host. Resolve any problems.
- ◆ For the host reboot issue, check the host to see why it failed to reboot.
- ◆ For the NSX service issue, log in to the NSX Manager UI, select **System > Appliances** and see if the host has an installation error. If so, you can resolve it from the NSX Manager UI. If the error cannot be resolved, you can refer to the upgrade logs to determine the cause of the failure.

Upgrade Fails Due to Insufficient Space in Bootbank on ESXi Host

NSX-T Data Center upgrade might fail if there is insufficient space in the bootbank or in the alt-bootbank on an ESXi host.

Problem

Unused VIBs on the ESXi host might be relatively large in size and therefore use up significant disk space. The unused VIBs can result in insufficient space in the bootbank or in the alt-bootbank during upgrade.

Solution

Uninstall the VIBs that are no longer required and free up additional disk space.

For more information on locating and deleting VIBs, see the VMware knowledge base article at <https://kb.vmware.com/s/article/74864>

Unable to Upgrade Host Placed in NSX Maintenance Mode

Host unit fails during the upgrade process and the upgrade coordinator places this host in NSX maintenance mode. Unable to upgrade host placed in NSX maintenance mode on restarting upgrade.

Problem

Hosts that fail during upgrade are placed in NSX maintenance mode.

Solution

- 1 Manually troubleshoot and fix the problem on the host.
- 2 From the NSX Manager UI, select **System > Fabric > Nodes > Host Transport Nodes**.
- 3 Locate the host that you fixed and select it.
The status of the host is maintenance mode.
- 4 Evacuate any VMs present on the host and restart the host.
- 5 Select **Actions > Exit Maintenance Mode**.

Failure to Upload the Upgrade Bundle

The upgrade bundle fails to upload because of insufficient disk space.

Solution

- 1 In the NSX Manager CLI, delete the unused files located at `/image/vmware/nsx/file-store/*` and `/image/core/*`.

Note Ensure that you do not delete the `/image/upgrade-coordinator-tomcat` folder or other folders located at `/image`.

- 2 From your browser, log in as a local admin user to an NSX Manager at `https://nsx-manager-ip-address/login.jsp?local=true`.
- 3 Select **System > Support Bundle** and delete any unused support bundles.

- 4 Reupload the upgrade bundle and continue with the upgrade process.

Backup and Restore During Upgrade

The Management Plane stops responding during the upgrade process and you need to restore a backup that was taken while the upgrade was in progress.

Problem

The Upgrade Coordinator has been upgraded and the Management Plane stops responding. You have a backup that was created while the upgrade was in progress.

Solution

- 1 Deploy your Management Plane node with the same IP address that the backup was created from.
- 2 Upload the upgrade bundle that you used at the beginning of the upgrade process.
- 3 Upgrade the Upgrade Coordinator.
- 4 Restore the backup taking during the upgrade process.
- 5 Upload a new upgrade bundle if necessary.
- 6 Continue with the upgrade process.

Loss of Controller Connectivity after Host Upgrade

Controller connectivity is lost after you upgrade your hosts.

Problem

After upgrading your host, when running post checks, your **Node Status** shows loss of connectivity to the controller.

Solution

- 1 Open an SSH session to the ESXi host experiencing the issue and confirm that none of the three NSX controllers are in a connected state. Run the `nsxcli -c get controllers` command.

Example response:

| Controller IP | Port | SSL | Status | Is Physical Master | Session State |
|-----------------|------|---------|--------------|--------------------|---------------|
| Controller FQDN | | | | | |
| 192.168.60.5 | 1235 | enabled | disconnected | true | down |
| nsxmgr.corp.com | | | | | |

In a working configuration, two controllers display the not used status and one controller has the connected status. If the NSX controller shows connected, refresh the UI and confirm that the status is green. If the controller shows not connected, continue to the next step.

- 2 Open an SSH session to one of the NSX Manager nodes as admin and run the `get certificate api thumbprint` command.

The command output is a string of alphanumeric numbers that is unique to this NSX Manager.

- 3 On the ESXi host, push the host certificate to the Management Plane:

```
ESXi1> nsxcli -c push host-certificate <NSX Manager IP or FQDN> username admin thumbprint
<thumbprint obtained in step #1>
```

When prompted, enter the admin user password for the NSX Manager. See the NSX-T Data Center *Command-Line Interface Reference* for more information.

- 4 Confirm the controller status is connected.

```
ESXi1> nsxcli -c get controllers
```

Confirm the controller connection state is green on the UI for this Transport Node.

If this issue continues, restart the following NSX services on the ESXi host:

```
ESXi1> /etc/init.d/nsx-opsagent restart
```

```
ESXi1> /etc/init.d/nsx-proxy restart
```

In-place Upgrade Fails

If an in-place upgrade fails for an ESXi 7.0 host, except when you see a PSOD, vMotion the VMs out of the host and then reboot the host.

Solution

- 1 Log in to vCenter Server and place the host in maintenance mode.
- 2 For an ESXi 7.0 host, use the following command to clear the upgrade status flag on the host:


```
nsxcli -c set host-switch upgrade-status false
```
- 3 vMotion the VM's out of the host.
- 4 Reboot the host and resume the upgrade process.

Upgrade Coordinator User Interface is Inaccessible

The Upgrade Coordinator user interface may not be accessible.

Problem

You cannot access the Upgrade Coordinator user interface or APIs.

Cause

Internal service dependencies may cause the Upgrade Coordinator user interface to become inaccessible.

Solution

Run the following command to restart the Upgrade Coordinator service:

```
restart service install-upgrade
```

NSX Manager User Interface is Inaccessible During Upgrade

The NSX Manager User Interface may be inaccessible when the Management Plane upgrade is in progress.

Problem

The NSX-T upgrade has been running longer than expected and the NSX Manager user interface is not accessible.

Cause

The NSX Manager user interface is inaccessible during the upgrade of the Management Plane.

Solution

The inaccessibility of the NSX Manager user interface does not necessarily indicate an upgrade failure. To verify the upgrade status, run the following command from the NSX-Manager CLI:

```
get upgrade progress-status
```

If you see an upgrade failure, follow the troubleshooting steps that are displayed in the command output.

Upgrading your NSX Federation Deployment

7

Follow the workflow for upgrading NSX Federation appliances depending on the version you are upgrading from.

Upgrading your NSX Federation Deployment from NSX-T Data Center 3.1 to NSX-T Data Center 3.2

First upgrade the Local Manager (LM) appliances from 3.1 to 3.2. The Global Manager (GM) and Local Managers continue to sync if they are at different versions between 3.1 and 3.2. Upgrade the Global Manager after the LM appliances. When upgrading the Global Manager, first upgrade the standby GM cluster, immediately followed by active GM cluster upgrade. Both active and standby Global Managers must have the same version.

Note During upgrade, the Global Manager version 3.1 can continue to sync with Local Managers already added to it that have been upgraded to version 3.2. However, if you change the LM certificate or add a new Local Manager version 3.2, to the Global Manager version 3.1, the version mismatch causes communication problems between the Global Manager and Local Manager. Do not change the LM certificate or add a new Local Manager version 3.2 to a Global Manager version 3.1. Before you change the LM certificate or add a new Local Manager version 3.2, upgrade the Global Manager to 3.2.

| Task | Instructions |
|--|--|
| Review the upgrade checklist before you begin. | Chapter 1 NSX-T Data Center Upgrade Checklist |
| Upgrade each Local Manager first. | Chapter 3 Upgrading NSX-T Data Center. |
| Upgrade the Global Manager appliance after all Local Managers are upgraded to NSX-T Data Center 3.2. When upgrading the Global Manager, first upgrade the standby GM cluster, followed by active GM cluster upgrade. | <ol style="list-style-type: none">1 Upgrade the Upgrade Coordinator.2 Upgrade Management Plane. |

Note When upgrading your NSX Federation deployment from NSX-T Data Center 3.2.1 or later to NSX-T Data Center 3.2.x, the upgrade is independent of the order of upgrade of the Global Manager and Local Manager appliances. The upgrade is also independent of the order of upgrade of the active and standby Global Manager clusters.

After rolling back or restoring a Global Manager node, make the following API call on each of the LM sites to force a sync between all LMs and the Global Manager:

```
POST <LM>/infra/full-sync-action?action=request_full_sync
```

Upgrading your NSX Federation Deployment from NSX-T Data Center 3.0.2 to NSX-T Data Center 3.1.0

First upgrade the Local Manager appliances from 3.0.2 to 3.1.0. The Global Manager and Local Managers continue to sync if they are at different versions between 3.0.2 and 3.1.0. Upgrade the Global Manager last.

Note During upgrade, the Global Manager at version 3.0.2 can continue to sync with Local Managers already added to it that have been upgraded to version 3.1.0. However, if you add a new Local Manager at version 3.1.0 to the Global Manager at version 3.0.2, the version mismatch causes communication problems between the Global Manager and Local Manager. Do not add a new Local Manager at version 3.1.0 to a Global Manager at version 3.0.2. To add a new Local Manager at version 3.1.0, first upgrade the Global Manager to 3.1.0.

| Task | Instructions |
|---|---|
| Review the upgrade checklist before you begin. | Chapter 1 NSX-T Data Center Upgrade Checklist |
| Upgrade each Local Manager first. | Chapter 3 Upgrading NSX-T Data Center. |
| Note While upgrading Local Managers from the Global Manager, you can change the Local Manager's orchestrator node but it takes some time for the change to reflect on the Global Manager UI. | |
| Upgrade the Global Manager appliance after all Local Managers are upgraded to NSX-T Data Center 3.1.0. | <ol style="list-style-type: none"> 1 Upgrade the Upgrade Coordinator. 2 Upgrade Management Plane. |