

VMware Workspace ONE UEM Mobile Content Management

VMware Workspace ONE UEM 1810



vmware®

You can find the most up-to-date technical documentation on the VMware website at:

<https://docs.vmware.com/>

If you have comments about this documentation, submit your feedback to

docfeedback@vmware.com

VMware, Inc.
3401 Hillview Ave.
Palo Alto, CA 94304
www.vmware.com

Copyright © 2018 VMware, Inc. All rights reserved. [Copyright and trademark information.](#)

Contents

- 1 Introduction to Mobile Content Management 5**
 - Requirements for Mobile Content Management 6

- 2 File Storage 9**
 - Content Management Enterprise Integration Solution 10
 - Set Content Storage Capacity 11
 - Restrict File Extensions 11

- 3 Corporate File Servers 13**
 - Enable End-User Access to Corporate File Server Content 14
 - Support for Corporate File Servers 14
 - Configure an Admin Repository 16
 - Enable Users to Sync Corporate File Servers 18
 - Configure Repository Details 19

- 4 Workspace ONE UEM Managed Content Repository 21**
 - Configure the Workspace ONE UEM Managed Content Category Structure 22
 - Upload Content to the Workspace ONE UEM Managed Repository 22
 - Upload Workspace ONE UEM Managed Content in Batches 23
 - Local File Storage for Workspace ONE UEM Managed Content 24
 - File Storage 24
 - File Storage Requirements 25
 - Enable File Storage for Content 26

- 5 Personal Content Repository 28**
 - Enable Personal Content 29
 - Roles for Folder Sharing 31
 - Configure Personal Content Quota Exceptions 31
 - File Encryption Migration 32

- 6 VMware Workspace ONE Content 33**
 - Configure VMware Workspace ONE Content 33
 - Configure Document Extensions 35
 - VMware Workspace ONE Content Capabilities by Platform 37
 - Matrix of Supported File Type by Platform 42

- 7 App Suite SDK Configurations 45**
 - Configure Default SDK Security Settings 46

[Expected Behavior for SDK Authentication](#) 53

8 [VMware Content App for Desktop](#) 55

[Enable VMware Content Locker Sync](#) 55

[Enable Personal Content Uploads in Socialcast](#) 56

9 [Workspace ONE UEM Application Deployment](#) 58

[Deploy Workspace ONE UEM Applications](#) 58

[Overview for Onboarding VMware Workspace ONE Content](#) 59

[Enable Onboarding for VMware Workspace ONE Content](#) 60

10 [Content Management using Workspace ONE Console](#) 61

[Menu Options for Content Management](#) 61

[Mobile Content Management Dashboard](#) 62

[Content Management List View](#) 62

[Options for Content Management](#) 63


[Settings for Content Management](#) 64

Introduction to Mobile Content Management

1

The Mobile Content Management™ (MCM) solution helps your organization address the challenge of securely deploying content to a wide variety of devices using a few key actions. Use the Workspace ONE UEM console to create, sync, or enable a file store known as a repository. Once configured this content deploys to end-user devices with the VMware Workspace ONE Content.

To understand how the content management works, review the following outline.



- 1 AirWatch Managed Content Repository** – Refers to a repository where Workspace ONE UEM administrators with the appropriate permissions have complete control over the files that get stored within it.

- 2 **Corporate File Server** – Refers to an existing repository that resides within an organization's internal network. Depending on an organization's structure, the Workspace ONE UEM administrator might or might not have administrator permissions for the corporate file server.
- 3 **VMware Workspace ONE Content** – Refers to the app that deploys to end-user devices, enabling access to content within the configured set of parameters.
- 4 **Personal Content** – Refers to a location where end users have complete control over the files that get stored within it.

Requirements for Mobile Content Management

Mobile Content Management (MCM) provides a flexible array of services to implement. Each service has its own unique set of requirements. Before configuring MCM, it is important to review the services you want to configure, and meet their basic requirements.

Component	Requirement & Description
Software and Hardware Requirements	
Supported Browsers	<p>The Workspace ONE Unified Endpoint Management (UEM) console supports the latest stable builds of the following web browsers.</p> <ul style="list-style-type: none"> ■ Chrome ■ Firefox ■ Safari ■ Internet Explorer 11 ■ Microsoft Edge <p>Note If using IE to access the UEM console, navigate to Control Panel > Settings > Internet Options > Security and ensure you have a security level or custom security level that includes the Font Download option being set to Enabled.</p> <p>If you are using a browser older than those listed above, upgrade your browser to guarantee the performance of the UEM console. Comprehensive platform testing has been performed to ensure functionality using these web browsers. The UEM console may experience minor issues if you choose to run it in a non-certified browser.</p>
Platform Requirements	<p>iOS 7.2 and later</p> <p>Android 3.2 and later</p> <p>Windows 7</p> <p>Windows 8</p> <p>Windows 10</p> <p>10.9 Mavericks and later</p>
Framework Requirements	<p>.NET 4.0.3 and later</p> <p>.NET 4.5 and later</p> <p>Mono</p>
Visual Studio Requirements	<p>Visual Studio 2010 v10.0.50903</p> <p>Visual C++ 2008</p>
Other	<p>Link Sharing enabled</p> <p>Microsoft Outlook 2007+ (32-bit or 64-bit)</p>
Role Requirements	

Component	Requirement & Description
Admin Roles	<p>Select a role that has Content, Content Device Install, and Content Device Remove enabled by default.</p> <p>Grants access the content management page and control of content distribution.</p> <p>For more information on creating roles, read the Roles and Added Resources Guide.</p>
End-User Roles	<p>Enable Manage Content and grant Full Access</p> <p>For more information on creating roles, read the Roles and Added Resources Guide.</p>
Repository Requirements	
AirWatch Managed Content	<p>Configure the category structure before uploading content</p> <p>You cannot add subcategories to categories that have content in them.</p>
Corporate File Server Content	<p>Install Content Gateway</p> <p>Install Content Gateway to establish a connection in instances where the Workspace ONE UEM server domain cannot access a Corporate File Server. See Support for Corporate File Servers to review which Workspace ONE UEM supported repositories require, support, or do not support Content Gateway.</p> <p>For comprehensive installation instructions, read the Content Gateway Installation Guide.</p>
Personal Content	<p>Purchase Appropriate Bundle or Service</p> <p>Not all content management packages include personal content management.</p>
Alternative File Storage Requirements	
Local File Storage	<p>Determine Appropriate Solution for Organization</p> <p>For more information on available options, see Local File Storage for Workspace ONE UEM Managed Content.</p>
Remote File Storage	<p>Determine Appropriate Solution for Organization</p> <p>For more information on available options, see Chapter 2 File Storage.</p> <p>Personal Content</p> <p>Current availability limited to content stored in the Personal Content repository. Not all content management packages include personal content management.</p> <p>Install Remote File Storage Server</p> <p>If using Remote File Storage as an alternative storage option for Personal Content, follow the installation instructions outlined in the Remote File Storage Installation Guide.</p>
Optional Security Component Requirements	
Content Rendering Engine	<p>Determine Appropriate Solution for Organization</p> <p>Leverage this product to address security concerns for content shared from the Self-Service Portal.</p> <p>Install Remote File Storage Server</p> <p>The Content Rendering Engine requires a working instance of the Remote File Server. Installation instructions are outlined in the Remote File Storage Installation Guide.</p> <p>Install Content Rendering Engine</p> <p>Follow the installation instructions outlined in the Content Rendering Engine Installation Guide.</p>
Onboarding	<p>Meet minimum app and OS requirements</p> <ul style="list-style-type: none"> ■ iOS VMware Workspace ONE Content v2.4+ ■ iOS 7+ device

Component	Requirement & Description
App Requirements	
Workspace ONE Content	Content Locker Sync

File Storage

Various content types are available for configuration in the Workspace ONE UEM console that can be deployed to the VMware Workspace ONE Contentapp on end-user devices. Although the content type does not impact the deployment location, back end storage varies by content type.

To gain insight about the storage options available for each content type, review the table. Learn about the additional configuration and components requirements for each storage option.

	Configurations	Components	Notes
Workspace ONE UEM Managed Content			
Workspace ONE UEM Database	X	X	
Local File Storage	√	√	Modify at a Global level Organization Group on-premises only
Corporate File Servers			
Workspace ONE UEM Database	X	X	Synced content only stores metadata on the Workspace ONE UEM Database
Network Repositories	√	√/X	Some repositories require Content Gateway. Requirements vary by repository type.
Personal Content			
Workspace ONE UEM Database	X	X	
Local File Storage	√	√	Modify at a Global level Organization Group on-premises only
Remote File Storage	√	√	Personal Content only

This chapter includes the following topics:

- [Content Management Enterprise Integration Solution](#)
- [Set Content Storage Capacity](#)
- [Restrict File Extensions](#)

Content Management Enterprise Integration Solution

The Content Management solution provides a suite of enterprise integration components designed to address the unique challenge of securing the content on mobile devices. The available Content Management components include Content Gateway, Remote File Storage (RFS), and Content Rendering Engine (CRE).

The Content Management solution provides a suite of enterprise integration components designed to address the unique challenge of securing the content on mobile devices. The available Content Management components include Content Gateway, Remote File Storage (RFS), and Content Rendering Engine (CRE).

Content Gateway

The Content Gateway, together with VMware Workspace ONE Content, lets your end users securely access content from an internal repository. This means that your users can remotely access their documentation, financial documents, board books, and more directly from content repositories or internal file shares. As files are added or updated within your existing content repository, the changes will immediately be reflected in VMware Workspace ONE Content, and users will only be granted access to their approved files and folders based on the existing access control lists defined in your internal repository. Using the Content Gateway with VMware Workspace ONE Content allows you to provide unmatched levels of access to your corporate content without sacrificing security.

Remote File Storage

Remote File Storage provides an on-premises storage alternative for Personal Content. Personal Content refers to a repository consisting of files uploaded and managed by end users. End users add files on their devices with VMware Workspace ONE Content, from any supported web browser with the Self-Service Portal, and from their personal computer with Content Locker Sync. By default, this content is stored in the Workspace ONE UEM database. For SaaS customers, that means Personal Content stores in the cloud by default. In some use cases, storing certain types of content in the cloud poses a security risk. Use Remote File Storage (RFS) to store Personal Content in a dedicated on-premises location.

Content Rendering Engine

The Content Rendering Engine (CRE) integrates with Remote File Storage to secure shared Personal Content. When an end user shares Personal Content from the Self-Service Portal, CRE converts the shared content into a rendered image of the source file. These shared images eliminate the need to download shared content, and enforce read-only permissions.

CRE enforces read-only permissions for the following file types.

■ Word (doc, docx)	■ BMP
■ Power Point (ppt, pptx)	■ PNG
■ Excel (xls, xlsx)	■ PDF
■ JPEG, JPG	■ Text

Set Content Storage Capacity

Storage capacity refers to the amount of space allocated for managed and personal content in an Organization Group and its child groups.

To set storage capacity:

- 1 Navigate to **Groups & Settings > All Settings > Admin > Storage** at a Customer or Global organization group level.
- 2 Select **Content** from the **Type** drop-down menu.
- 3 Select the **Edit** icon. Complete the settings.

Setting	Description
Organization Group Name	Specify the group to which you want to apply content storage restrictions.
Capacity	Set maximum storage space in MB allocated to content stored in the Workspace ONE UEM database. The default storage for Workspace ONE Content provided by VMware AirWatch to SaaS customers is 5 GB.
Overage Allowed	Enter the amount of overage you want to allow, if any. For SaaS customers, this value is not configurable.
Max File Size	Use the default value of 200 MB as the maximum size for uploads. If operating against this recommendation, 2 GB is the upper limit.
Encryption	Encrypt the content with AES - 256 file level encryption. Enabling encryption triggers the File Encryption Migration scheduler to begin migrating any unencrypted data it finds.

- 4 Select **Save**.

Restrict File Extensions

Specify file type permissions by creating a whitelist or blacklist for Managed, Corporate File Server, and Personal content. This restriction hides blocked file types based on their extension from being visible in the UEM console or within Workspace ONE Content and so prevents them from being downloaded or uploaded to Content Repositories.

- 1 Navigate to **Content > Settings > Advanced > File Extensions**.

2 Set the **Allowed File Extensions**.

Setting	Description
Whitelist	Enter the file extensions you want to include. Separate extensions using a new line, a comma, or a space.
Blacklist	Enter the file extensions you want to exclude. Separate extensions with a line break, a comma, or a space.
All	Select to allow any file type for upload or sync.

3 Select **Save** to apply the configuration.

Once restrictions are applied, you can anticipate the following responses.

Response	Who	What	Where	Repository
Error Message	Administrator	Manually adds a restricted file to the content repository	Console	AirWatch Managed
Error Message	End User	Manually adds a restricted file	Device	Personal Content
Silent interaction	Administrator	Syncs with a corporate file server that contains a restricted file	Console	Corporate File Server
Silent interaction	End User	Syncs with a corporate file server that contains a restricted file	Device (throughWorkspace ONE Content)	Corporate File Server

Corporate File Servers

The Content Management solution supports integration with your Corporate File Servers (CFS). Corporate File Servers refer to existing repositories that reside within an organization's internal network.

Features

Corporate File Server integration supports the following features:

- Secure integration
- Protect access to organization's internal network
- Advanced integration options using Content Gateway and Remote File Storage

Security

The Content Management solution provides the following security options:

- SSL encryption for data transit
- Control access and download rights of Workspace ONE UEM administrators
- Content stored within organization's network
- Only metadata stored in Workspace ONE UEM database. Support for review and management of the stored metadata.

Deployment

Depending on an organization's structure, the Workspace ONE UEM administrator might or might not have administrative permissions for a CFS. After the Content Management solution is integrated with CFS, the end-user devices can sync the content from the servers using VMware Workspace ONE Content.

This chapter includes the following topics:

- [Enable End-User Access to Corporate File Server Content](#)
- [Support for Corporate File Servers](#)
- [Configure an Admin Repository](#)

- [Enable Users to Sync Corporate File Servers](#)
- [Configure Repository Details](#)

Enable End-User Access to Corporate File Server Content

Sync your network's existing corporate file servers with Workspace ONE UEM by configuring an Admin Repository, an Automatic User-Added Repository, or a Manual User-Added repository. The available configurations impact the trigger that initiates the syncing of content to devices.

Use this macro-level configuration overview to gain insight into the start-to-finish process of enabling end-users access to the Corporate File Server content.

- 1 Configure a repository in the UEM console.
- 2 Download the configured Content Gateway installer.
- 3 Run the Content Gateway installer.
- 4 Verify connectivity between the UEM console and Content Gateway.
- 5 Evaluate your organization's need for multiple Content Gateway nodes. Global organizations with concerns about latencies caused by geographical separations can use this functionality.
- 6 Configure an Admin repository or sync Corporate File Servers (CFS) in the UEM console.
If configuring an Admin Repository, select **Test Connection** to ensure connectivity.
- 7 Configure VMware Workspace ONE Content in the UEM console.
- 8 Deploy Workspace ONE UEM Applications to your device fleet.

Support for Corporate File Servers

Workspace ONE UEM supports integration with various corporate file servers. The syncing method support and requirement of the Content Gateway component vary by repository type.

Available Sync Methods

Review the available syncing methods for repositories:

- **Admin** – Refers to a repository that gets fully configured and synced by an administrator in the UEM console.
- **Automatic** – Refers to a repository that gets configured by an administrator in the UEM console, but gets synced by end users on their devices.
- **Manual** – Refers to a repository that gets configured in the UEM console, but relies on the end user to add the link manually and sync the repository on their device.

Corporate File Server Matrix

Use the matrix to determine the supported syncing methods and Content Gateway requirements by repository type:

	Admin	Automatic	Manual
Available Repositories			
Box	✓	✓	✓
CMIS	✓	✓	✓
Google Drive	✓	–	–
Network Share	✓	✓	✓
OneDrive	✓	–	–
OneDrive for Business	✓	–	–
OneDrive for Business ADFS	✓	–	–
OneDrive for Business OAuth	✓	–	–
SharePoint	✓	✓	✓
SharePoint ADFS	✓	✓	✓
SharePoint O365	✓	✓	✓
SharePoint O365 ADFS	✓	✓	✓
SharePoint O365 OAuth	✓	✓	✓
SharePoint - Personal (My Sites)	✓	–	–
SharePoint WebDAV	✓	–	–
SharePoint Windows Auth	✓	✓	✓
WebDAV	✓	✓	✓
Access through Content Gateway			
Box	–	–	–
CMIS	✓+	✓+	✓+
Google Drive	–	–	–
Network Share	✓+	✓+	✓+
OneDrive	–	–	–
OneDrive for Business	✓	–	–
OneDrive for Business ADFS	✓	–	–
SharePoint	✓	✓	✓
SharePoint ADFS	✓	✓	✓
SharePoint O365	✓	✓	✓
SharePoint O365 ADFS	✓	✓	✓
SharePoint - Personal (My Sites)	✓	–	–

	Admin	Automatic	Manual
SharePoint WebDAV	✓	–	–
SharePoint Windows Auth	✓	✓	✓
WebDAV	✓	✓	✓
Document Extensions			
Box	✓	✓	✓
CMIS	✓	✓	✓
Google Drive	✓	–	–
Network Share	✓*	✓*	✓*
OneDrive	✓	–	–
OneDrive for Business	✓	–	–
OneDrive for Business ADFS	✓	–	–
OneDrive for Business OAuth	✓	–	–
SharePoint	✓**	✓**	✓**
SharePoint ADFS	✓**	✓**	✓**
SharePoint O365	✓**	✓**	✓**
SharePoint O365 ADFS	✓**	✓**	✓**
SharePoint O365 OAuth	✓	✓	✓
SharePoint - Personal (My Sites)	✓**	–	–
SharePoint WebDAV	✓**	–	–
SharePoint Windows Auth	✓**	✓**	✓**
WebDAV	✓*	✓*	✓*

Legend:

¥ =The VMware Content Gateway on Linux servers supports only SMB v2.0 and SMB v3.0. The default supported version is SMB v2.0.

✓+ = Required

✓ = Supported

– = Not Supported

✓* = Supported, with limitations. Access limited to files from repositories previously opened in the VMware Workspace ONE Content.

✓** = Supported, with limitations. Access limited to files previously downloaded in the Workspace ONE Content.

Configure an Admin Repository

Configure an Admin Repository to sync your network's existing corporate file servers with Workspace ONE UEM. After the sync, end users can access the Corporate File Server content from their devices.

To configure an Admin Repository:

- 1 Navigate to **Content > Repositories > Admin Repositories** in the UEM console.

- 2 Select **Add**.
- 3 Configure the settings that appear:

Setting	Description
Name	Label the content directory.
Type	Select a Corporate File Server from the drop-down menu.
Link	Provide the full path to the directory location rather than the root domain. Example: http://SharePoint/Corporate/Documents A URL copied directly from a web browser might not have permission to access a server for certain repository types.
Organization Group	Assign Corporate File Server access to a selected group of users.
Authentication Type	Select the access level admins have to Corporate File Servers from the UEM console. <ul style="list-style-type: none"> ■ None – Prevent administrators from viewing and downloading Corporate File Server content from the UEM console. ■ User – Permit browsing of the repository file structure within the UEM console. Enter credentials into the Username and Password text boxes that appear.
Access via Content Gateway	Use the Content Gateway if the Workspace ONE UEM server's domain cannot access the Corporate File Server.
Content Gateway	Identify the unique name of the appropriate Content Gateway node from the drop-down menu.
Allow Inheritance	Permit child organization groups to inherit the same access permissions as their parent organization group.
Allow Write	Permit end users to create and upload files and folders, edit documents, and check in or check out files to external repositories on their devices.
Allow Delete	Permits remote content delete for the Network Share repository. With this feature, the end user can delete their content permanently from the Network Share repository using the Workspace ONE Content.

- 4 Select **Test Connection** to verify connectivity. A successful test result indicates the corporate file server integrated successfully.
- 5 Enter the values in the remaining text boxes under the Security, Assignment, and Deployment tabs. Select **Save**.

Link Configuration Best Practices

This specific rule applies to SharePoint 2013, Office 365, and the later versions. Some URLs cannot be accessed using applications and services, and can only be accessed using a web browser. If a 'browser only' URL gets entered as the link when configuring Content Gateway, the connection fails.

To ensure that Content Gateway gets configured with the correct link, follow the procedure:

- 1 Enter the URL in the browser.
- 2 Navigate to **PAGE > Edit Properties > View Properties**.
- 3 Right click and copy link address.
- 4 Paste the address into the **Link** text box in the UEM console.

Enable Users to Sync Corporate File Servers

Integrate Workspace ONE UEM with existing content repositories by configuring an Automatic or Manual Template that end users sync to from their devices. After the sync, end users access the Corporate File Server content from their devices.

The steps can vary when configuring an Automatic or Manual Template.

- 1 Navigate to the appropriate page in the UEM console:

Corporate File Server Type	Location
Automatic Template	Content > Repositories > Templates > Automatic
Manual Template	Content > Repositories > Templates > Manual

- 2 Select **Add**.
- 3 Complete the text boxes that appear. The text boxes can change when configuring an Admin Repository, an Automatic Template, or a Manual Template.

Setting	Description
Name	Label the content directory.
User Repository Name (auto template only)	Use look-up values to name the repository after the end user within the VMware Workspace ONE Content.
Type	Select a Corporate File Server from the drop-down menu.
Link	A URL copied directly from a web browser might not have permission to access a server for certain repository types.
Link (auto template only)	Use look-up values to create a repository when an end user accesses the VMware Workspace ONE Content. Example: https://sharepoint.acme.com/share/{EnrollmentUser}
Link (manual template only)	Provide the path to the directory location using * as a wildcard for a domain link. Example: http://*.sharepoint.com
Organization Group	Assign Corporate File Server access to a specified group of users.
Access via Content Gateway	Use the Content Gateway if the Workspace ONE UEM server's domain cannot access the Corporate File Server.
Allow Inheritance	Allow child organization groups to inherit the same access permissions as their parent organization group.
Allow Write	Allow end users to create and upload files and folders, edit documents, and check in or check out files to external repositories on their devices.

- 4 Complete the remaining Security, Assignment, and Deployment tabs and select **Save**.
- 5 If configuring a **Manual Template**, direct end users to the Self Service Portal where they can manually add and access their repository.

Configure Repository Details

Configure the Security, Assignment, and Deployment details to ensure the content in the Managed and Corporate File Server repositories remain secure.

- 1 On the Security tab, complete the text boxes to control how the end users share and move sensitive documents outside of corporate mediums. The Force Encryption setting has been removed since Workspace ONE UEM console version 9.5. The VMware Workspace ONE Content app encrypts all the files by default, whether the setting is available or not.

Setting	Description
Document Sharing	Disable the sharing settings for maximum security. You can enable them for configuring end-user collaboration.
Access Control	Set to Allow Offline Viewing to give end users the most viewing freedom for their document. Configure Allow Online Viewing Only to ensure that all devices accessing content are compliant, as Workspace ONE UEM cannot scan offline devices for compliance.
Allow Open in Email	Allow the content to open in emails.
Allow Open in Third Party Apps	Give the permission to open this content in other applications. You can set a list of approved apps in the SDK Profile. Disabling this option also disables the end user's permission to print the PDF documents from the iOS VMware Workspace ONE Content.
Allow Saving to Other Repositories	Select to allow your end users to save this file to their Personal Content.
Enable Watermark	Select to add a watermark overlay to the file. Configure the Overlay Text for the watermark as part of an SDK profile.
Allow Printing	Give the end users the permission to print PDF documents from the iOS VMware Workspace ONE Content using AirPrint server. Once printed, content falls out of the control of the Workspace ONE UEM administrator. Printing is supported only if Allow Open in Third Party Apps is enabled.
Allow Edit	This setting only applies to write-enabled repositories.

- 2 Configure the **Assignment** settings to control which users have access to content. This function ensures that only authorized employees have access to confidential or sensitive material and allows you to set up a tiered hierarchy of content access.

Setting	Description
Device Ownership	Define as Any , Corporate-Dedicated , Corporate-Shared , Employee Owned or Undefined .
Organization Groups	To assign the content to a new group, start typing in the text box.
User Groups	Designate groups if you are integrating with Directory Services or custom user groups.

3 Use the **Deployment** settings to control how and when your end users access content.

Setting	Description
Transfer Method	Specify Any method or Wi-Fi Only from the drop-down menu. Restricting transfers to Wi-Fi forces devices to check in with Workspace ONE UEM to ensure compliance.
Download While Roaming	Enable to allow your end users to download the content while roaming.
Download Type	Set to deploy content one of two ways: <ul style="list-style-type: none"> ■ Automatically – Installs on devices when content becomes available. ■ On Demand – Installs on devices only at the end user's request.
Download Priority	Define to let your end users know if the content download is Normal , High , or Low priority.
Required	Select to flag the content as required in the VMware Workspace ONE Content. End users must download and review the required content in order for their devices to maintain compliance with Workspace ONE UEM.
Effective Date	Specify to configure a limited range of content availability.
Expiration Date	Specify to configure a limited range of content availability.

4 Select **Save**.

Workspace ONE UEM Managed Content Repository

4

The Workspace ONE UEM Managed Content repository refers to a location where administrators with the appropriate permissions have complete control over the files that gets stored within it. The end users can access the added content using VMware Workspace ONE Content in the repository labeled AirWatch Managed.

Features

Managed Content repository provides the following features:

- Uploading of files manually
- Options to configure and provide permissions for individual files
- Sync options to control content accessed on end-user devices
- List View for advanced file management options

Security

To protect the content that is stored and synced from the repository to end-user devices, the following security features are available:

- SSL encryption secures data during transit between the UEM console and end-user devices
- Roles with the security pin for controlled access to the content

Deployment

The Managed repository content is stored in the Workspace ONE UEM database. You can choose to host the database in the Workspace ONE UEM cloud or on-premises, depending on your deployment model. For more information, see [Configure the Workspace ONE UEM Managed Content Category Structure](#).

This chapter includes the following topics:

- [Configure the Workspace ONE UEM Managed Content Category Structure](#)
- [Upload Content to the Workspace ONE UEM Managed Repository](#)
- [Upload Workspace ONE UEM Managed Content in Batches](#)

- [Local File Storage for Workspace ONE UEM Managed Content](#)

Configure the Workspace ONE UEM Managed Content Category Structure

Content categories help keep the AirWatch Managed repository content organized in the UEM console and the Workspace ONE Content. Configure the category structure for the Workspace ONE UEM Managed content before uploading content to the UEM console.

To add a category:

- 1 Navigate to **Content > Categories > Add Category**.
- 2 Configure the settings that appear and **Save**.

Setting	Description
Managed By	Select the organization group or groups you want to apply the category.
Name	Enter a name that is easily recognizable and applies to a clear set of content.
Description	Provide a brief description of the category.

To add a subcategory to your category structure:

- 1 Select **Add**  from the **Action Menu**.
- 2 Configure the settings that appear and **Save**.

Setting	Description
Managed By	Review the organization group of the parent category that populates by default.
Name	Enter a name that is easily recognizable and applies to a clear set of content.
Description	Provide a brief description of the subcategory.

Upload Content to the Workspace ONE UEM Managed Repository

Add files to the Managed Content repository by manually uploading and configuring them in the UEM console. The repository stores its content in the Workspace ONE UEM database by default, and syncs with the VMware Workspace ONE Content app, delivering content to end users' devices.

To upload files:

- 1 Navigate to **Content > List View**.
- 2 Select **Add Content** and choose **Select Files**.
- 3 Select an individual file for the upload from the dialog box.

4 Configure content **Info** settings.

Setting	Description
Name	Review the filename that automatically populates in this text box.
Organization Group	Review the organization group to which this content deploys.
File	Review the file that populates in this text box.
Storage Type	Ensure that the text box displays AirWatch Managed.
Version	Ensure that the version number is 1.0 as you are adding this content to the UEM console for the first time. You can upload new versions from the Action menu in the AirWatch Managed List View.
Description	Provide a description of the files you upload.
Importance	Set the content importance as High , Normal , or Low .
Category	Map the uploaded content to a configured Category.

5 Provide additional metadata about the content in the **Details** settings.

Setting	Description
Author	Name the author of the file.
Notes	Provide notes on the file.
Subject	Provide a subject.
Keywords	List keywords and topics that this file covers.

6 Configure the content.

Upload Workspace ONE UEM Managed Content in Batches

Use batch imports to bypass external file share integration in a dedicated SaaS or on-premises deployment with a hardened network.


To upload a batch import:

- 1 Navigate to **Content > Batch Status**.
- 2 Select **Batch Import**.
- 3 Provide a **Batch Name** and a **Batch Description**.
- 4 To download a .csv template file, select the information icon ()
- 5 Fill out the CSV file with the file path and other information for content you want to upload.
- 6 Select **Choose File** and choose the .csv that you created.
- 7 Select **Open** to select the .csv.
- 8 Select **Save** to upload your populated Batch File.

Local File Storage for Workspace ONE UEM Managed Content

Local File Storage separates the managed content from the Workspace ONE UEM database, storing it in a dedicated, on-premises location with a connection to the Workspace ONE UEM instance.

Managed content is stored in the Workspace ONE UEM database by default. However, uploading a large volume of managed content can cause issues with the database performance. In this case, on-premises customers can free up space in the database by moving the managed content to an integrated Local File Storage solution.



File Storage

Certain Workspace ONE UEM functionality uses a dedicated file storage service to handle processing and downloads, which reduces the overall burden on your Workspace ONE UEM database and increases its performance. Configuring file storage manually is only applicable to on-premises customers. It is automatically configured for SaaS customers.

It also includes certain Workspace ONE UEM reports, internal application deployment, and Workspace ONE UEM-managed content. When you enable file storage for any of these functionalities, it is applied to the others automatically. Setting up file storage causes all reports, all internal applications, and all managed content to be stored there.

Workspace ONE UEM Reports

As of console version 9.0.2, three new reports were added that appear the same as existing reports but use a revamped back-end framework. This new framework generates reports with greater reliability and faster download times. To take advantage of these benefits, you must set up file storage.

For more information about these reporting updates, see the following Knowledge Base article: <https://support.air-watch.com/articles/115002346928>.

Internal Applications

When file storage is enabled, all internal application packages that you upload through the UEM console are stored in a file storage location.

File storage is required to deploy Win32 applications (IPA, PAK, APPX, MSI, EXE, and so on) and macOS applications (.dmg, .pkg, .mpkg, and so on) from the Apps & Books area of the UEM console. This feature is called software distribution.

Workspace ONE UEM Managed Content

You can separate the managed content from the Workspace ONE UEM database by storing it in a dedicated file storage location. Uploading large amounts of managed content might cause issues with database performance. In this case, on-premises customers can free up space in the database by moving the managed content to an integrated local file storage solution.

Personal content also moves to the file storage solution is enabled. By default, personal content is stored in the SQL database. If you have a Remote File Storage enabled, personal content is stored in the RFS and not in the file storage or SQL database.

File Storage Requirements

Separate the managed content from the Workspace ONE UEM database by storing it in a dedicated File Storage. To set up a file storage, you must determine the location and storage capacity for your file storage, configure the network requirements, and create an impersonation account.

Important File Storage is required for Windows 10 Software Distribution.

Create the Shared Folder on a Server in Your Internal Network

- File storage can reside on a separate server or the same server as one of the other AirWatch application servers in your internal network. It is only accessible to components that require access to it, such as the Console and Device Services servers.
- If the Device Services server, Console server, and the server hosting the shared folder are not in the same domain, then establish Domain Trust between the domains to avoid the authentication failure. If the Device Services server or Console server is not joined to any domain, then supplying the domain during service account configuration is sufficient.

Configure the Network Requirements

- **If using Samba/SMB** – TCP: 445, 137, 139. UDP: 137, 138
- **If using NFS** – TCP and UDP: 111 and 2049

Allocate Sufficient Hard Disk Capacity

Your specific storage requirements may vary depending on how you plan to use file storage. The file storage location should have enough space to accommodate the internal apps, managed content, or reports you intend to use. Take into the account the following considerations.

- If you enable caching for internal apps or content, then a best practice is to size the Device Services server for 120 percent of the cumulative size of all the apps/content you need to publish.
- For storing reports, your storage requirements depend on the number of devices, the daily amount of reports, and the frequency with which you purge them. As a starting point, you should plan to allocate at least 50 GB for deployment sizes up to 250,000 devices running about 200 daily reports. Adjust these numbers based on the actual amount you observe in your deployment. Apply this sizing to your Console server as well if you enable caching.

Create a Service Account with Correct Permissions

- Create an account with read and write permissions to the shared storage directory.
- Create the same local user and password on the Console, Device Services, and the server that is being used for File Storage.
- Give the local user read/write/modify permissions to the file share that is being used for the File Storage Path.
- Configure the File Storage Impersonation User in AirWatch with the local user.

You can also use a domain service account instead of a local user account.

Configure File Storage at the Global Organization Group

Configure file storage settings at the Global organization group level in the UEM Console.

Enable File Storage for Content

Configure the file storage to store your managed content.

Procedure:

- 1 At the Global organization group level, navigate to **Groups & Settings > All Settings > Installation > File Path** and scroll to the bottom of the page.

- 2 Select the **File Storage Enabled** slider and configure the settings. When file storage is enabled, you can configure an external repository in which files are stored. A disabled setting means that files are stored as binary large objects in the database.

Setting	Description
File Storage Path	Enter the path files are to be stored in the following format: \\{Server Name}\{Folder Name}, where Folder Name is the name of the shared folder you create on the server.
File Storage Caching Enabled	<p>When enabled, a local copy of files requested for download is stored on the Device Services server as a cache copy. Subsequent downloads of the same file retrieve it from the Device Services server as opposed to file storage.</p> <p>If you enable caching, consider accommodating for the amount of space needed on the server. For more information, see File Storage Requirements.</p> <p>If you integrate with a CDN, then apps and files are distributed through the CDN provider, and a local copy is not stored on the Device Services server. For more information, refer to the VMware Workspace ONE UEM CDN Integration Guide (https://resources.air-watch.com/view/8cr52j4hm6xft4v2wgg/en).</p>
File Storage Impersonation Enabled	Select to add a service account with the correct permissions.
File Storage Impersonation Username	Provide a valid service account user name to obtain both read and write permissions to the shared storage directory.
Password	Provide a valid service account password to obtain both read and write permissions to the shared storage directory.

- 3 Select the **Test Connection** button to test the configuration.

Personal Content Repository

The Content Management solution provides the end users with options to manage their personal content on enrolled devices. The Personal Content repository is a location where end users have complete control over the files that are stored within it. Only the deployments that purchased the appropriate licenses can configure the security permissions that enable this repository for end users.

Features

When the Personal Content repository is enabled, the end users are provided with the following capabilities:

- Upload and download the personal content to the repository.
- Access repository content from multiple mediums.
- Manage the personal content stored in the repository.

Accessibility

The end users can access and upload the content to the repository using:

- VMware Workspace ONE Content application
- Supported web browser with the Self-Service Portal
- Personal computer with VMware Content Locker Sync

Security

To protect the personal content of end users, Content Management solution provides the following security features:

- The data in transit is secured using SSL encryption.
- The content that is stored and deployed in the Personal Content repository is protected with AES 256-bit encryption.
- VMware Workspace ONE Content v2.2 and later for iOS uses the NSFileProtectionComplete class to store the content.

Deployment

Depending on the deployment model, you can store Personal Content repository files in the Workspace ONE UEM database that is hosted on-premises or in the cloud. Alternatively, you can use the Remote File Storage to store the personal content on-premises, regardless of the deployment model.

Storage

The Content Management solution provides you the options to allocate and manage the storage quota for the Personal Content repository. You can also configure individual user storage quotas in the UEM Console at **Groups & Settings > All Settings > Content > Personal Content**.

This chapter includes the following topics:

- [Enable Personal Content](#)
- [Roles for Folder Sharing](#)
- [Configure Personal Content Quota Exceptions](#)
- [File Encryption Migration](#)

Enable Personal Content

Personal Content repository serves as a dedicated storage location for the content uploaded by the end user. Enable Personal Content on the Workspace ONE UEM console and set the storage space required for the repository. You can also enable link sharing and folder sharing, set email alerts when folders are shared, and configure the data loss prevention settings.

- 1 At a Customer level Organization Group, navigate to **Groups & Settings > All Settings > Content > Personal Content**.
- 2 Set Personal Content to **Enabled** to create a personal content repository, and configure the available fields.
- 3 Configure **Storage Allocations**.

Setting	Description
Storage Quota	Divide the allocated storage between the Workspace ONE UEM Managed and Personal Content repositories, dedicating an amount of the available storage to Personal Content. By default, all available storage gets dedicated to Personal Content, indicated by the far-right position of the slider.
User Quota	Set the maximum amount of storage any one user can consume, in MB. This quota applies to users in the same Organizational Group hierarchy as Storage Quota.
User Group Quota(s)	Select Add New and configure storage exceptions on a user group basis.

- Configure Shared Links by setting Link Sharing to **Enabled** and enabling the options that appear. Once enabled, end users can share files as links from the VMware Workspace ONE Content and the Self-Service Portal.

Setting	Description
Link Sharing	Enable link sharing of documents.
Auto Expire Days	Enable and fill in a numerical value to specify the number of Days links remain available for sharing. Disable to leave the option open for end users to configure when they share their links.
Auto Expire Downloads	Enable and input a numerical value to set the maximum number of Downloads before the link expires. Disable to leave the option open for end users to configure when they share their links.
Require Password Protection	Enable and set the Minimum Length in characters and the Complexity of the password. Disable to leave the option open for end users to configure when they share their links.

- Configure Shared Folders by setting Folder Sharing to **Enabled** and enabling the options that appear. Once enabled, end users can share folders from the VMware Workspace ONE Content and the Self-Service Portal.

Setting	Description
Share with User Groups	Enable to share folders with entire user groups instead of manually listing each user.
Available Sharing Roles	Set the roles available to end users sharing their folders.
Share with External Users	Enable end users to share folders with users external to their Organization Group.
Available Sharing Roles	Set the access privilege role for those users that end users share a folder with. See the Roles for Folder Sharing matrix, for an overview of sharing roles and their permissions.
User Quota	Leave the quota at 0 to have all external user uploads count against the folder sharer's quota. Set a quota to give external users dedicated space for uploads.

- Configure **Email Notifications**.

Setting	Description
Email Notifications	Enable to alert users through email when a folder is shared with them.

- Set the Data Loss Prevention settings to **Disabled** for maximum security, or set it to **Enabled** for collaboration.

Setting	Description
Allow Open in Email	Enable to allow content to open in emails. Disable for maximum security.
Allow Open in Third Party Apps	Enable to open personal content in other applications. You can set a list of approved apps in the SDK Profile. Disabling this option also disables the end user's permission to print the PDF documents from the iOS VMware Workspace ONE Content. Disable for maximum security.

Setting	Description
Allow Printing	Enable iOS devices to print personal content PDFs using AirPrint. Printing is supported only if Allow Open in Third Party Apps is enabled. Disable for maximum security.
Watermark	Enable to apply a dynamic watermark to the files rendered in the HTML5 Viewer. By default, the user's email is applied as the file's watermark. You can reconfigure the watermark text in the SDK.

8 Select **Save** to complete your configuration.

Roles for Folder Sharing

Folder sharing roles refer to the permissions that end users can assign when sharing a folder. These permissions apply to the user group or external user with whom an end user shares a folder.

	Owner	Co-Owner	Editor	Reader	Viewer
View File and Folders	✓	✓	✓	✓	✓
Download Files to Computer	✓	✓	✓	✓	
Add Comments to Files	✓	✓	✓	✓	✓
Upload Files to Folder	✓	✓	✓		
Delete Files or Subfolders	✓	✓	✓		
Edit Files	✓	✓	✓		
View Other Folder Collaborators	✓	✓	✓		
View Other Collaborators Activity in Feed	✓	✓	✓	✓	
Modify Sharing of Folder	✓	✓			
Generate Shared Links to Files	✓				
Transfer Folder Ownership	✓				

Configure Personal Content Quota Exceptions

Use the User Storage screen to edit storage quotas for end users on an individual basis, and perform additional management actions. These edited settings provide a final layer of granularity, and override any limits set when configuring Personal Content.

- 1 Navigate to **Groups & Settings > All Settings > Content > User Storage**.
- 2 To override user storage on an individual level, select **Edit**. It takes precedence over Organization group or user group storage quota configurations.
- 3 Select **Delete** to enter a PIN and delete a user's content. A PIN configuration is in place to protect the user content from administrators who might unintentionally delete it.

File Encryption Migration

Collect the unencrypted content and migrate it to an encrypted state on a scheduled basis using the File Encryption Migration scheduler. Use the default schedule values that are populated. However, administrators with the correct roles, can access and change these settings.

You can review the default values of the File Encryption Migration scheduler task on the **AdminScheduler** page in a Tenant Organization Group. If necessary, you can also configure a custom schedule.

VMware Workspace ONE Content

6

The Content Management solution provides you the VMware Workspace ONE Content app to enable the end users to access the managed content. The Workspace ONE Content app is deployed to end-user devices and the managed content is accessed in the app within the configured parameters.

Features

- Content settings to set unique app behaviors.
- Use default SDK settings when configured as part of the AirWatch app suite.
- Content Management Dashboard and list views to manage the content deployment from the UEM console.

Security

- SSL encryption for secure data transit.
- AES 256-bit encryption to protect the deployed content.
- VMware Workspace ONE Content v2.2 and later for iOS uses the NSFileProtectionComplete class to store the content.

This chapter includes the following topics:

- [Configure VMware Workspace ONE Content](#)
- [Configure Document Extensions](#)
- [VMware Workspace ONE Content Capabilities by Platform](#)
- [Matrix of Supported File Type by Platform](#)

Configure VMware Workspace ONE Content

Provide end users with device side access to the corporate content using the Workspace ONE Content app. The configurations set in the UEM console determine the level of freedom provided to end users accessing corporate content from their devices.

- 1 Navigate to **Groups & Settings > All Settings > Content > Applications > Content Locker**.

2 Configure the **Settings and Policies** settings.

Setting	Description
Application Profile	Set to define the security policies and settings used by this application. Leave as Default and configure the Recommended Default SDK settings to define app behavior using Workspace ONE UEM recommendations. Alternatively, select Custom application settings to override the default SDK settings and configure a unique set off behaviors for the app.
iOS Profile	Select a custom-created SDK profile from the drop-down list.
Android Profile	Select a custom-created SDK profile from the drop-down list.
Use Legacy Settings and Policies	Only enable legacy settings if directed to do so by a Workspace ONE UEM representative. Legacy settings do not leverage Shared SDK profile settings and should only be implemented in certain edge cases.
Default Authentication Method	Select the authentication method for the applications.
Enable "Keep me signed in"	Enable to allow end users to remain signed in between uses.
Maximum Number of Failed Attempt	Set the number of passcode entry attempts allowed before all data in the Workspace ONE Content will be wiped from a device.
Authentication Grace Period (min)	Enter the time (in minutes) after closing the Workspace ONE Content before reopening the Workspace ONE Content will require users to enter credentials again.
Prevent Compromised Devices	Enable to prevent compromised devices from accessing Workspace ONE Content.
Enable Offline Login Compliance	Enable to allow offline login compliance.
Maximum Number of Offline Logins	Enter the number of offline logins allowed before you have to go online.

3 Configure the **General** settings.

Setting	Description
Numbers of Days to Keep Content New	Select the number of days recently added documents will be labeled as new in the Workspace ONE Content.
Block Enrollment via Content Locker, Boxer, and Browser	Enable to prevent enrollment through Workspace ONE Content, VMware Workspace ONE Boxer, and VMware Workspace ONE Web. If Workspace ONE Content uses the VMware Workspace ONE SDK for iOS in Objective-C, then MDM enrollment is required for the single-sign on SDK setting to function correctly.
Change Repository Name	Enable to change the repository name in the Root Repository Name field that appears.
Root Repository Name	Enter the new repository name you want to use.
Allow Hyperlinks	Enable to allow end users to open hyperlinks located in documents in the Open Internet Links with field that appears.
Open Internet Links with	Select the application in which to open hyperlinks.

Setting	Description
Local Storage	Enable to provide a storage alternative for user content. Local storage saves on the device and doesn't sync with other Personal Content in the cloud. Disable local storage to force all user content to save in a location that syncs with other Personal Content in the cloud.
Upload on Wi-Fi Only	Enable to restrict uploads from Workspace ONE Content to Wi-Fi connections only.

- 4 Implement the **Terms of Use** agreement for your app.
- 5 Assign **Notifications** to Workspace ONE Content applications for the specified platform:

Setting	Description
Application Type	Indicate as System or Internal .
Application Name	Assign to the application.
Bundle ID	Assign to the application.
Badge Count	Set to Required , Updates Only or None . Required: Badge Count represents the number of required documents that the User has not opened through the Workspace ONE Content. (Windows Only) The Badge Count tracks the 'read' status for required documents per user across multiple devices. When a user with multiple devices reads a required document, then all other devices reflect the document as read. Updates Only (For Downloaded Content): Badge Count represents the number of downloaded documents that have updates or new versions available. None: Badge Counts are disabled for Workspace ONE Content.

- 6 Select **Save**.

Configure Document Extensions

Document extensions enable end users to interact with the VMware Workspace ONE Content files from within third-party applications. This functionality requires specific configurations within the UEM console and special consideration for certain types of corporate file servers.

Ensure that document extension functionality appears on devices with Workspace ONE Content v3.1 and later by completing the required configurations in the UEM console.

Disable Application Whitelisting

- 1 Navigate to **Apps > Settings and Policies > Security Policies**.
- 2 Set **Limit Documents to Open Only in Approved Apps** to **No**.
- 3 Select **Save**.

Enable Open Into

Open Into option must be enabled for the end users to use the export functionality within Microsoft Office 365 apps.

- 1 Navigate to **Content > Repositories > Admin Repositories**.
- 2 Select the **Edit** icon next to the Corporate File Server that syncs to end-user devices.
- 3 On the **Security** tab, select **Allow Open In Third Party Apps** and then **Save**.

(Android Only) Enable Storage Access from Third-Party Apps

If you are using Android SDK Default settings:

- 1 Navigate to **Apps > Settings and Policies > Settings > Custom Settings**.
- 2 Select **Enable Custom Settings** and paste {"PolicyEnableFileProvider": "true"}.
- 3 Select **Save**.

If you are using a custom SDK profile for Workspace ONE Content:

- 1 If you have an existing custom profile, navigate to **Apps > Settings > Profiles > Custom Profile > Custom Settings Payload**.
- 2 If you want to add a custom profile, navigate to **Apps > Settings > Profiles > Add Profile > SDK Profile > Android > Custom Settings > Custom Settings Payload**.
- 3 Paste {"PolicyEnableFileProvider": "true"} and select **Save**. If you have multiple custom settings, append the PolicyEnableFileProvider key after your existing custom key within {}. For example, {"CustomSetting Default": "true", "PolicyEnableFileProvider": "true" }

(Android Only) Limitation of Storage Access from Third-Party Apps

- Allow Open in third-party apps flag is considered to allow or deny access to third-party apps. 'Allow Email' permission flag is not considered for a file since it cannot be determined (based on application ID) whether the third-party app is an email app or not.
- Support for Android framework to provide the Content file and storage access from third-party apps is disabled by default to manage app containers and the data shared between them.
- Local Storage files are not accessible since Open In functionality for third-party apps is disabled by default.
- When Workspace ONE Content authentication is enabled, you must have Workspace ONE Content unlocked to access it through a third-party app (displays message).
- If your admin has configured an app whitelist and the third-party app is not whitelisted, then you cannot open or create files through Workspace ONE Content.

- For the Managed content, all the content is available while browsing through a third-party app. For other repositories, content is available (for one level) only for those folders that are synced in Workspace ONE Content.

VMware Workspace ONE Content Capabilities by Platform

The following matrix applies to the platform version of VMware Workspace ONE Content available in the app store.

Features	iOS	Android	Win 10	Win 8
Security				
Authentication				
Basic	✓	✓	✓	✓
AD/LDAP	✓	✓	✓	✓
Token	✓	✓	✓	✓
Second Factor Passcode	✓	✓	✓	✓
Encryption				
SSL Encryption in Transit	✓	✓	✓	✓
AES 256-Bit Encryption at Rest	✓	✓	✓	✓
In Memory Encryption	✓	✓		
FIPS 140-2	✓	✓	✓	✓
Certificate Pinning	✓			
IT Policies				
Compromised Detection	✓	✓	✓	✓
Automatic offline revocation when device is compromised	✓	✓		
Require Enrollment	✓	✓	✓	✓
Automatic offline revocation when document expires	✓	✓	✓	✓
Maximum number of offline logins	✓	✓	✓	✓
Wipe content at Maximum number of failed login attempts	✓	✓	✓	✓
Prevent deleting mandatory content	✓	✓	✓	✓
DLP				
Prevent Copy/Paste	✓	✓	✓	✓
Enable/Disable Print	✓			
Enable/Disable Open in Third Party Application(s)	✓	✓	✓	✓
Enable/Disable Sharing via Email	✓	✓		
Enable/Disable Document Level Encryption	✓	✓	✓	✓

Features	iOS	Android	Win 10	Win 8
Enable/Disable Document Watermarking	✓*	✓*		
*The watermark feature is available for only admin repositories, user repositories, and Workspace ONE UEM managed content. It is not available for Personal Content and email attachments opened in Workspace ONE Content				
Enable/Disable Screen Capture		✓**		
** For Workspace ONE Content, Enable Screen Capture must be set to Yes to allow users to take screenshot of the documents and media content. It also enables the Screen Mirroring feature using third party apps like Vysor. If Enable Screen Capture is set to No, users can only take screenshot of the Workspace ONE Content home screen and folders. Screen Mirroring is also disabled.				
Data Collection				
Install Content	✓	✓	✓	✓
Open/Close Content	✓	✓	✓	✓
Uninstall/Delete Content	✓	✓	✓	✓
Session Status	✓	✓	✓	✓
Mobile Experience				
Access				
Keep Me Signed In	✓	✓	✓	✓
Authenticate with back-end credentials (Active Directory)	✓	✓	✓	✓
Integrate with Workspace ONE UEM Single-Sign-On	✓	✓		✓
Workspace ONE UEM Single-Sign-On with Hub as Broker App	✓	✓		✓
Allow Offline Access	✓	✓	✓	✓
Standalone MCM	✓	✓	✓	✓
Customize Terms of Use	✓	✓	✓	✓
Content Views				
Featured Content (Folder, File, Category)	✓	✓	✓	✓
All Content (All/Installed/Uninstalled)	✓	✓	✓	✓
Recent Activity (Recently Updated and Viewed)	✓	✓	✓	✓
New Content	✓	✓	✓	✓
Favorite Content	✓	✓	✓	✓
Tile and List Views of content	✓		✓	✓
Full-screen mode for images/PDFs	✓	✓	✓	✓
View Required Content	✓		✓	✓
Swipe through all images in a folder/view	✓			
Grid view of all images	✓			
File Management				

Features	iOS	Android	Win 10	Win 8
Sort Content (alphabetically, chronologically, importance)	✓	✓	✓	✓
Filter Content (File Type, download status)	✓	✓	✓	✓
Delete On-Demand documents	✓	✓	✓	✓
Import and Upload new documents/new versions	✓	✓	✓	✓
2-way sync for WebDav, network shares	✓	✓		
2- way sync for Google Drive, One Drive	✓	✓		
Check-In/Check-Out to SharePoint	✓	✓		
Add comments to files at SharePoint Check-in		✓		
User Generated Content- Capture Pictures or Video in VMware Workspace ONE Content	✓	✓		
Add, Copy, Multi-Select files or folders	✓	✓	✓	
User Generated Content – Add Audio Files	✓			
User Generated Content – Add Office Files	✓	✓		
User Generated Content – Add Text Files	✓	✓		
Queue Multiple Document Downloads Simultaneously	✓	✓	✓	
Manage Downloads (Pause/Resume/Cancel/Re-order)	✓		✓	
Manage Uploads (Pause/Resume/Cancel/Re-order)	✓			
Usability				
Search Strings within Documents (PDF Only)	✓	✓	✓	✓
Thumbnail navigation/scrub bar	✓		✓	✓
View Table of Contents	✓	✓	✓	✓
Multi-Tab Document Viewing(File type restrictions apply)	✓		✓	
Bookmarking (PDF Only)	✓	✓	✓	✓
Edit Bookmarks	✓		✓	✓
Night-Mode (PDF)	✓		✓	✓
Presentation Mode (native pointer for presenting content)	✓			
Support for Links in PDFs	✓	✓	✓	✓
View Updates	✓	✓	✓	✓
Search Documents Based on Keywords	✓	✓	✓	✓
Highlight search results	✓	✓	✓	✓
View Last Successful Sync (Sync Status)	✓	✓	✓	✓
User Managed Content (Personal/Local Storage)				

Features	iOS	Android	Win 10	Win 8
Personal Content Policies				
Enable/Disable access to Personal Content	✓	✓	✓	✓
Storage quota control by user and group	✓	✓	✓	✓
Store Personal Content in Remote File Storage (RFS)	✓	✓	✓	✓
Enable/Disable Link Sharing	✓	✓	✓	✓
Enforce link sharing polices for max days, max downloads, password	✓	✓	✓	✓
Enable/Disable Folder Sharing	✓	✓	✓	✓
File Management				
Add/Remove Files(s)	✓	✓	✓	✓
Add new version	✓	✓	✓	✓
Move File(s)/Folder(s)	✓	✓	✓	✓
Add/Remove Folder(s)	✓	✓	✓	✓
Removed files goes to Trash	✓	✓	✓	✓
Open external files into Personal Content	✓	✓	✓	✓
Automatically Upload document upon opening in VMware Workspace ONE Content	✓	✓		
Collaboration				
Add and Save PDF Annotations	✓	✓	✓	✓
Edit and Save Office Documents (Word, Excel, PPT)	✓	✓		
Generate and share links to Personal Content from the device	✓	✓	✓	✓
Share Personal Content Folders and Add Collaborators from device	✓	✓	✓	✓
View shared folders with Files (Co-Owner, Editor, Reader)	✓	✓	✓	✓
Display Collaborators & Roles by each Shared Folder	✓	✓	✓	✓
Add Comments to File Versions	✓			
View Activity Feed of Comments & Revision History per Document	✓			
Save Drafts locally	✓			
Notify User when update is available for document	✓	✓	✓	✓
Customization and Integration				
External File Repository Integration				
Share Point 2007	✓	✓	✓	✓

Features	iOS	Android	Win 10	Win 8
Share Point 2010	✓	✓	✓	✓
Share Point 2013	✓	✓	✓	✓
Share Point Online (Office 365)	✓	✓	✓	✓
Network File Share	✓	✓	✓	✓
WebDAV	✓	✓		✓
FileServer (HTTP)	✓	✓		✓
Google Drive	✓	✓	✓	✓
OneDrive	✓	✓	✓	✓
CMIS	✓	✓		✓
User Added Repository Support	✓	✓	✓	✓
One Drive for Business	✓	✓		
Box	✓	✓	✓	
Localization				
Arabic	✓	✓	✓	✓
Chinese - Simplified	✓	✓	✓	✓
Chinese - Traditional	✓	✓	✓	✓
Czech	✓	✓	✓	✓
Danish	✓	✓	✓	✓
Dutch	✓	✓	✓	✓
English	✓	✓	✓	✓
French	✓	✓	✓	✓
Hebrew	✓	✓	✓	
German	✓	✓	✓	✓
Italian	✓	✓	✓	✓
Japanese	✓	✓	✓	✓
Korean	✓	✓	✓	✓
Polish	✓	✓	✓	✓
Portugese - Brazil	✓	✓	✓	✓
Russian	✓	✓	✓	✓
Spanish	✓	✓	✓	✓
Swedish	✓	✓	✓	✓
Turkish	✓	✓	✓	✓
Email Attachment and Integration				
Allow Viewing of Attachments and saving to VMware Workspace ONE Content	✓	✓	✓	✓

Features	iOS	Android	Win 10	Win 8
Allow Viewing, Extracting and Saving of zipped attachments to VMware Workspace ONE Content	✓	✓	✓	
Allow Editing of Email Attachments	✓	✓		
Allow Reshare of Email Attachments	✓	✓		
Multi-Select Content and Send as Email Attachments (Individual Attachments)	✓			
Select Folders and Send as Email Attachments (Zipped Folder)	✓			
VMware Browser Integration				
Allow Viewing and Saving of VMware Browser Downloads	✓	✓		
*File type supported for editing.				

Matrix of Supported File Type by Platform

The following matrix applies to the version of VMware Workspace ONE Content available in the app store.

Supported File Types	iOS	Android	Windows 10
AD/Azure RMS	✓	✓ Workspace ONE Content v3.5+	
AAC (audio/aac)	✓	✓	
ALAC (audio/m4a)	✓	✓	
WAV (audio/wav)	✓	✓	
MP3 (audio/mpeg)	✓	✓	
MOV (video/quicktime)	✓	✓	
MP4 (video/mp4)	✓	✓	
M4B, M4R,	✓		
M4V	✓	✓	
CSV (.csv)	✓ View only	✓ View only	✓ View only
ePub (.epub)	✓		
iBooks			
iWorks - Keynote (.key) application/vnd.apple.keynote	✓ View Only		
iWorks - Numbers (.numbers) application/vnd.apple.numbers	✓ View Only		

Supported File Types	iOS	Android	Windows 10
iWorks - Pages (.pages) application/vnd.apple.pages	✓ View Only		
MS Office - Excel (.xls/.xlsx) application/vnd.ms-excel	✓ Edit Only	✓ Edit Only	✓
XLSM	✓	✓	
MS Office - PowerPoint (.ppt/.pptx) application/vnd.ms-powerpoint	✓ Edit Only	✓ Edit Only	✓
PPTM	✓		
MS Office - Word (.docx) application/msword Editing is not supported for .doc files	✓ Edit Only	✓ Edit Only	✓
DOCM	✓		
MS Office - Password Protected (.docx, .pptx, .xlsx MS Office 2007 or later) Editing is not supported for .doc files	✓ Edit Only	✓	
HTML (.html) text/html	✓	✓	✓
PDF (.pdf) application/pdf	✓ Edit Only	✓ Edit Only	✓
Rich Text Format (.rtf) application/rtf	✓	✓	
Rich Text Format Directory (.rtfd) application/octet-stream	✓		
XML (.xml) application/xml	✓	✓	✓
PNG (.png) image/png	✓	✓	✓
JPG (.jpg) image/jpeg	✓	✓	✓
TIF (.tif, .tiff) image/tif	✓	✓	✓
Bitmap (.bmp) image/bmp	✓	✓	✓
GIF (.gif) image/gif	✓	✓	✓
Zip (.zip) application/zip	✓	✓	✓
Password Protected Zip	✓	✓	✓
RAR (.rar) application/rar	✓		
Password Protected RAR			
GZIP (.gzip) application/zip		✓	
BZIP (.bzip) application/zip			
BZIP2 (.bzip2) application/zip		✓	
TAR (.tar) application/zip		✓	
TXT	✓	✓	✓
MSG	✓		

*File type supported for editing**View only, presentation mode not available

**View only, presentation mode not available

App Suite SDK Configurations

When you configure your application, you select a custom or a default application profile. This action applies an SDK profile to the application, giving deployed Workspace ONE UEM applications additional features.

To ensure your application configuration runs smoothly, it is helpful to:

- Know the difference between a Custom and Default SDK profile.
- Determine if a Custom or a Default SDK profile is more appropriate for your application.
- Ensure you have configured the SDK profile type that you want to apply.

Use the following chart to determine if you want to apply a **Default** or **Custom** SDK profile to your application, and to direct you to the configuration instructions for the profile you use.

You can define SDK profiles using two different profile types: **Default** or a **Custom** SDK application profile.

	Default	Custom
Implementation	Share SDK profile settings across all applications set up at a particular organization group (OG) or below.	Apply SDK profile settings to a specific application, and override the Default Settings SDK profiles.
Advantage	Provides a single point of configuration for all of your apps in a particular OG and its child groups.	Offers granular control for specific applications and overrides the Default Settings SDK profiles.
Configure	Groups & Settings > All Settings > Apps > Settings and Policies > Security Policies	Groups & Settings > All Settings > Apps > Settings and Policies > Profiles
Read More	Continue reading this section to learn which default SDK profiles apply to deployed apps.	Learn more about custom SDK profile settings in the VMware Workspace ONE UEM Mobile Application Management Guide .

This chapter includes the following topics:

- [Configure Default SDK Security Settings](#)
- [Expected Behavior for SDK Authentication](#)

Configure Default SDK Security Settings

Default SDK settings apply across Workspace ONE UEM and wrapped applications, providing a unified user experience on devices. Because the configured SDK settings apply to all Workspace ONE UEM and wrapped applications by default, you can configure the default SDK profile with the entire Workspace ONE UEM and wrapped application suite in mind.

Not all platforms or Workspace ONE UEM applications support all available default SDK profile settings. A configured setting only works on the device when it is supported by the platform and app. This also means that an enabled setting might not work uniformly across a multi-platform deployment or between applications. The SDK Settings matrix covers the available SDK profile settings and the apps and platforms they apply to.

Key Assumptions

The recommendations provided apply to an app suite that includes:

-
- VMware Workspace ONE Web
 - VMware Workspace ONE Content
 - Enrolled devices
 - Workspace ONE UEM or wrapped apps
 - SDK settings
-

- 1 Navigate to **Groups & Settings > All Settings > Apps > Settings and Policies > Security Policies**.
- 2 Configure **Security Policies**.

Action	Description	Rec
Authentication Type		
Passcode	Prompt end users to authenticate with a user-generate passcode when the app first launches, and after an app session timeout. Enabling or disabling SSO determines the number of app sessions that get established.	–
Username and Password	Prompt end user to authenticate by re-entering their enrollment credentials when the app first launches, and after an app session timeout. Enabling or disabling SSO determines the number of app sessions that get established.	–
Disabled	Allow end user to open apps without entering credentials.	√
SSO		
Enabled	Establish a single app session across all Workspace ONE UEM and Workspace ONE UEM wrapped apps.	√
Disabled	Establish app sessions on a per app basis.	–
Offline Access		
Enabled	Allow end users to open and use Workspace ONE UEM and wrapped apps when disconnected from Wi-Fi. Offline Workspace ONE UEM apps cannot perform downloads, and end users must return online for a successful download. Configure the Maximum Period Allowed Offline to set limits on offline access.	√
Disabled	Remove access to Workspace ONE UEM and wrapped apps on offline devices.	–

Compromised Protection		
Enabled	Override MDM protection. App level Compromised Protection blocks compromised devices from enrolling, and enterprise wipes enrolled devices that report a compromised status.	√
Disabled	Rely solely on the MDM compliance engine for compromised device protection.	–
Data Loss Prevention		
Enabled	Access and configure settings intended to reduce data leaks.	√
	Enable Copy And Paste	
	Allows an application to copy and paste on devices when set to Yes .	
	Enable Printing	
	Allows an application to print from devices when set to Yes .	
	Enable Camera	
	Allows applications to access the device camera when set to Yes .	
	Enable Composing Email	
	Allows an application to use the native email client to send emails when set to Yes .	
	Enable Data Backup	
	Allows wrapped applications to sync data with a storage service like iCloud when set to Yes .	
	Enable Location Services	
	Allows wrapped applications to receive the latitude and longitude of the device when set to Yes .	
	Enable Bluetooth	
	Allows applications to access Bluetooth functionality on devices when set to Yes .	
	Enable Screenshot	
	Allows applications to access screenshot functionality on devices when set to Yes .	
	Enable Watermark	
	Displays text in a watermark in documents in the VMware Workspace ONE Content when set to Yes. Enter the text to display in the Overlay Text field or use lookup values. You cannot change the design of a watermark from the UEM console.	
	Limit Documents to Open Only in Approved Apps	
	Enter options to control the applications used to open resources on devices. (iOS only) You can use Workspace ONE UEM Configuration values to restrict users from importing files from third-party applications into Workspace ONE Content. For more information, see Configure Import Restriction in Workspace ONE Content section.	
	Allowed Applications List	
	Enter the applications that you allow to open documents.	
Disabled	Allow end user access to all device functions.	–

- 3 **Save.**
- 4 Navigate to **Groups & Settings > All Settings > Apps > Settings and Policies > Settings.**

5 Configure **Settings**.

Branding		
Enabled	Apply specific organizational logo and colors, where applicable settings apply, to the app suite.	–
Disabled	Maintain the Workspace ONE UEM brand throughout the app suite.	√
Logging		
Enabled	Access and configure settings related to collecting logs.	√
Logging Level		
Choose from a spectrum of recording frequency options:		
<ul style="list-style-type: none"> ■ Error – Records only errors. An error displays failures in processes such as a failure to look up UIDs or an unsupported URL. ■ Warning – Records errors and warnings. A warning displays a possible issue with processes such as bad response codes and invalid token authentications. ■ Information – Records a significant amount of data for informational purposes. An information logging level displays general processes as well as warning and error messages. ■ Debug – Records all data to help with troubleshooting. This option is not available for all functions. 		
Send logs over Wi-Fi only		
Select to prevent the transfer of data while roaming and to limit data charges.		
Disabled	Do not collect any logs.	–
Analytics		
Enabled	Collect and view useful statistics about apps in the SDK suite.	√
Disabled	Do not collect useful statistics.	–
Custom Settings		
Enabled	Apply custom XML code to the app suite.	–
Disabled	Do not apply custom XML code to the app suite.	√

6 **Save**.

(iOS Only) Configure Import Restriction in Workspace ONE Content

You can use the configuration keys in UEM console to restrict import of content from third-party applications into the Workspace ONE Content. The configuration keys can be used to allow content import from only whitelisted set of native applications. Use the following configuration keys to restrict or allow content import from third-party applications into Workspace ONE Content.

Configuration Key	Value Type	Supported Values	Description
<code>{"ContentImportRestriction"}</code>	Boolean	true = restriction enabled false = restriction disabled For example, <code>{"ContentImportRestriction": true}</code>	When enabled, device users cannot import content from any non-whitelisted third-party applications including the native iOS applications into the Workspace ONE Content.
<code>{"ContentImportAllowNativeApps"}</code>	Boolean	true = import from native applications are allowed false = import from native applications are not allowed For example, <code>{"ContentImportAllowNativeApps": true}</code>	When enabled, the device users can import content from native applications when the import restriction is enabled.

The `ContentImportRestriction` and `ContentImportAllowNativeApps` configuration values can be used in combination to configure the import restriction as per your requirement. If you want to allow import of content from all native apps, enable the `ContentImportAllowNativeApps` key. The `ContentImportAllowNativeApps` key is enabled by default and allows import from all native apps such as iOS native Email, Files, Safari, AirDrop, and such. When enabled, the device users can open and import content from non-whitelisted apps into Workspace ONE Content using the web versions of the non-whitelisted applications (using Safari).

If you want to allow only specific applications, disable the `ContentImportAllowNativeApps` key and add the allowed applications in the whitelist.

If you want to restrict importing of content from specific native apps, disable the `ContentImportAllowNativeApps` key and add the allowed native applications in the whitelist.

Note The Limit Documents to Open Only in Approved Apps option must be enabled in the Data Loss Prevention settings before enabling the configuration key values. Safari and AirDrop cannot be whitelisted as there is no associated bundle ID.

If you are using SDK Default settings:

- 1 Navigate to **Group & Settings > All Settings**.
- 2 From All Settings, navigate to **Apps > Settings & Policies > Settings**.
- 3 Select **Enable Custom Settings** and paste the configuration keys as per your requirement. For example, to allow import only from native apps, `{"ContentImportRestriction": true, "ContentImportAllowNativeApps": true}`.
- 4 To allow importing from a specific list of apps (whitelist):
 - a Navigate to **Settings & Policies > Security Policies**.
 - b Select the **Allowed Applications List** text box and list the applications you want to allow the users to import content into the Workspace ONE Content.
- 5 Select **Save**.

If you are using a custom SDK profile for Workspace ONE Content:

- 1 Navigate to **Group & Settings > All Settings**.
- 2 If you have an existing custom profile, navigate to **Apps > Settings & Policies > Profiles > Custom Profile > Custom Settings**.
- 3 If you want to add a custom profile, navigate to **Apps > Settings & Policies > Profiles > Add Profile > SDK Profile > iOS > Custom Settings**.
- 4 From Custom Settings, select **Configure** and paste the configuration keys as per your requirement. For example to allow import only from native apps, { "ContentImportRestriction": true, "ContentImportAllowNativeApps": true}.
- 5 From the Restriction section, select **Restrict documents** to be opened in following apps and add the list of apps that you want to allow as per your requirement (whitelist).
- 6 Select **Save**.

(iOS Only) Configure PDF Autosave in Workspace ONE Content

From Workspace ONE Content v4.13.2, the device users can enable or disable the PDF Autosave functionality by using the Enable PDF Autosave setting in the Workspace ONE Content app. The PDF Autosave setting is disabled by default. The PDF Autosave function can be set to 30 seconds, 60 seconds, and 120 seconds respectively using the Autosave time in seconds setting in the Workspace ONE Content. The administrators can use the configuration key provided by VMware AirWatch in the AirWatch Console to force enable the PDF Autosave functionality in Workspace ONE Content. When enabled using the configuration key, the device users cannot disable the PDF Autosave function and the Enable PDF Autosave setting is unavailable in the Workspace ONE Content. When the PDF Autosave function is enabled, the changes made to a PDF file when an autosave is in progress are not saved. After every instance of an autosave, the PDF document is reloaded.

Use the following configuration key to enable PDF Autosave function in Workspace ONE Content:

Configuration Key	Value Type	Supported Values	Description
{ "ContentPDFAutoSaveEnabled" }	Boolean	true = enabled false = can be enabled or disabled by the device user	When set to True, the PDF Autosave functionality is enabled and the device users cannot disable the setting. The Enable PDF Autosave setting in the Workspace ONE Content is unavailable to the device users.

If you are using SDK Default settings:

- 1 Navigate to **Group & Settings > All Settings**.
- 2 From All Settings, navigate to **Apps > Settings & Policies > Settings**.
- 3 Select **Enable Custom Settings** and paste the configuration keys as per your requirement. For example, to enable PDF Autosave, { "ContentPDFAutoSaveEnabled": true }.

4 Select **Save**.

If you are using a custom SDK profile for Workspace ONE Content:

- 1 Navigate to **Group & Settings > All Settings**.
- 2 If you have an existing custom profile, navigate to **Apps > Settings & Policies > Profiles > Custom Profile > Custom Settings**.
- 3 If you want to add a custom profile, navigate to **Apps > Settings & Policies > Profiles > Add Profile > SDK Profile > iOS > Custom Settings**.
- 4 From Custom Settings, select **Configure** and paste the configuration keys as per your requirement. For example, to enable PDF Autosave, { "ContentPDFAutoSaveEnabled": true }.
- 5 Select **Save**.

(iOS and Android Only) Configure Privacy Settings for Workspace ONE Content

Use the configuration keys in the UEM console to perform additional privacy disclosure and data collection practices. End users who are upgrading or are starting to use the latest version of Workspace ONE Content are presented with new privacy dialog screen upon the application launch. For more information about the privacy notice and data sharing settings, see <https://support.workspaceone.com/articles/360005402834>.

The privacy dialog screen lets the user know the following information:

- Data collected by the app – Provides a summary of data that is collected and processed by the application. Some of this data is visible to administrators of the Workspace ONE UEM administration console.
- Device Permissions – Provides a summary of device permissions requested for the app to enable product features and functionality, such as push notifications to the device.
- Company's privacy policy – By default, a message is displayed to the user to contact their employer for more information. You can configure the privacy policy URL in the UEM console. Once configured, the user can access the employer's privacy policy from the app.

Use the following configuration keys to enable privacy notice and data sharing settings in Workspace ONE Content:

Configuration Key	Value Type	Supported Values	Description
{ "DisplayPrivacyDialog" }	Integer	0 = disabled 1 = enabled (default)	When set to '1' (enabled), Workspace ONE Content displays a privacy notice to the users about the data that is collected and the permissions that are required on the device for the optimal functioning of the app.
{ "PolicyAllowFeatureAnalytics" }	Integer	0 = disabled 1 = enabled (default)	When set to '1' (enabled), Workspace ONE Content displays a notice to the users about the option to opt-in to anonymous feature usage analytics that help VMware improve product functionality and invent new product capabilities. When set to '0', the data sharing notice is not displayed and no data is collected from the device to optimize the app experience.
{ "PolicyAllowCrashReporting" }	Boolean	True = enabled False = disabled	When set to True, app crashes are reported back to VMware.
{ "PrivacyPolicyLink" }	String	"https://www.url.com"	Provide the Policy URL that you want your users to visit when Your company's privacy policy is selected from the Privacy notice.

If you are using SDK Default settings:

- 1 Navigate to **Group & Settings > All Settings**.
- 2 From All Settings, navigate to **Apps > Settings & Policies > Settings**.
- 3 Select **Enable Custom Settings** and paste the configuration keys as per your requirement. For example, to enable Crash reporting, { "PolicyAllowCrashReporting": true}.
- 4 Select **Save**.

If you are using a custom SDK profile for Workspace ONE Content:

- 1 Navigate to **Group & Settings > All Settings**.
- 2 If you have an existing custom profile, navigate to **Apps > Settings & Policies > Profiles > Custom Profile > Custom Settings**.
- 3 If you want to add a custom profile, navigate to **Apps > Settings & Policies > Profiles > Add Profile > SDK Profile > iOS > Custom Settings**.
- 4 From Custom Settings, select **Configure** and paste the following configuration keys as per your requirement.

5 Select **Save**.

(iOS Only) Disable Screen Timeout for Workspace ONE Content

Use the configuration keys in the UEM console to restrict device users from disabling the screen timeout in Workspace ONE Content app.

Configuration Keys	Value Type	Supported Values	Description
{ "PolicyAllowScreenTimeoutToggle" }	Boolean	True (default) = Enabled False = Disabled	Set to True or False to control the timeout setting in Content app. If a value is not set, the default setting is applied and users can switch the timeout setting. When set to false, users are not allowed to toggle the timeout setting.

If you are using SDK Default settings:

- 1 Navigate to **Group & Settings > All Settings**.
- 2 From All Settings, navigate to **Apps > Settings & Policies > Settings**.
- 3 Select **Enable Custom Settings** and paste the configuration keys as per your requirement. For example, to disable screen timeout, { "PolicyAllowScreenTimeoutToggle": false }
- 4 Select **Save**.

If you are using a custom SDK profile for Workspace ONE Content:

- 1 Navigate to **Group & Settings > All Settings**.
- 2 If you have an existing custom profile, navigate to **Apps > Settings & Policies > Profiles > Custom Profile > Custom Settings**.
- 3 If you want to add a custom profile, navigate to **Apps > Settings & Policies > Profiles > Add Profile > SDK Profile > iOS > Custom Settings**.
- 4 From Custom Settings, select **Configure** and paste the configuration keys as per your requirement. For example, to disable screen timeout, { "PolicyAllowScreenTimeoutToggle": false }
- 5 Select **Save**.

Expected Behavior for SDK Authentication

Enabling or disabling SSO determines the number of app sessions established, impacting the number of authentication prompts end users receive.


Authentication Type	SSO	Sessions	Credentials	Expected Behavior
Disabled	Enabled	Single	Enrollment Credentials	Open apps without prompting end users to enter credentials.

Passcode	Enabled	Single	Passcode	Prompts at first launch of first app, establishing a single app session. The next authentication prompt occurs after the session times out.
Username and Password	Enabled	Single	Enrollment Credentials	Prompts at first launch of first app, establishing a single app session. The next authentication prompt occurs after the session times out.
Passcode	Disabled	Per App	Passcode	Prompts on a per app basis, establishing individual app sessions. Note that each app may have a unique passcode. The next authentication prompt occurs when launching a new app, or an individual app session times out.
Username and Password	Disabled	Per App	Enrollment Credentials	Prompts on a per app basis, establishing individual app sessions. The next authentication prompt occurs when launching a new app, or an individual app session times out.

VMware Content App for Desktop

8

The VMware Content Locker Sync app is an app for the desktop that syncs the content to a designated folder on an end user's PC or Mac computer with the Personal Content repository. In addition to the end user's personal computer, synced content becomes accessible to an end user from any browser through the Self-Service Portal, and on mobile devices using the VMware Workspace ONE Content application.



- 1 Workspace ONE UEM administrator enables and configures Personal Content in the Workspace ONE UEM console.
- 2 Workspace ONE UEM administrator sets the end-user availability of the Content Locker Sync and manages associated security configurations from the UEM console.
- 3 End users download and use the app, available in the Self-Service Portal, at their own discretion.

Enterprise Deployments of VMware Content Locker Sync

Administrators implementing an enterprise deployment of the Content Locker Sync can configure the MSI installer and provide the functionality prepackaged on the desktop.

This chapter includes the following topics:

- [Enable VMware Content Locker Sync](#)
- [Enable Personal Content Uploads in Socialcast](#)

Enable VMware Content Locker Sync

Enable the sync functionality of the Content Locker Sync app and configure the settings to allow end users to download the app from the Self-Service Portal.

To enable and configure the Sync Client and its basic features:

- 1 Navigate to **Groups & Settings > All Settings > Content > Applications > VMware Content Locker Sync**.
- 2 **Enable** or **Disable** features to set the sync client behavior.

Setting	General
VMware Content Locker Sync	Enable sync functionality associated with the product.
Client Download	Enable the end-user sync client downloads from the Self-Service Portal. Disable the end-user sync client downloads if implementing an enterprise deployment of Content Locker Sync using the MSI installer.
Require MDM Enrollment	Enable a requirement for end users to have managed devices to authenticate successfully into Content Locker Sync. This requirement does not apply to end users who authenticated before the configuration of this setting.

- 3 Select the **Terms of Use agreement** for Windows.
- 4 If implementing Client Downloads, verify that the appropriate **Link Sharing** settings are enabled.

Enable Personal Content Uploads in Socialcast

Integration with Socialcast allows the end user upload their Personal Content to Socialcast. Integration requires configurations in both the UEM console and the Socialcast Admin Console.

Generating an API token in the UEM Console

- 1 Navigate to **Groups & Settings > All Settings > System > Advanced > API > Rest API > Add**.
- 2 Complete the text boxes that appear.

Setting	Description
Service	Enter Socialcast as the service name.
Account Type	Select Admin from the drop-down menu.
API Key	Copy the key that automatically generates. Upload this key into Socialcast.

- 3 Select **Save** to generate your token.

Uploading the API token in the Socialcast Admin Console

- 1 Log into the Socialcast Admin Console.

For more information on setting up a Socialcast Community, see <http://developers.socialcast.com/admin/setting-up-a-socialcast-community/>.

- 2 Navigate to the **Security** tab.

For more information on Security configurations for Socialcast, see <http://developers.socialcast.com/admin/customizing-the-community/security/#restrict-attachments>.

- 3 Enable Workspace ONE Content attachments and complete the text boxes.

Setting	Description
AirWatch Domain	Provide the URL of your Workspace ONE UEM instance.
API Key	Paste the API key you copied from the UEM console into the text box.

Workspace ONE UEM Application Deployment

9

Control how Workspace ONE UEM applications deploy to your end users and other security configurations from the UEM console. Once deployed, end users can download and use these apps.

The **VMware Workspace ONE UEM Mobile Application Management (MAM) Guide** covers the process for deploying public applications in full detail. While the VMware Workspace ONE Content application is available in the public app store, your organization needs to purchase licenses per device to take advantage of the Workspace ONE UEM MCM solution. Please see <http://www.air-watch.com/pricing> or contact Workspace ONE Support for more information.

This chapter includes the following topics:

- [Deploy Workspace ONE UEM Applications](#)
- [Overview for Onboarding VMware Workspace ONE Content](#)
- [Enable Onboarding for VMware Workspace ONE Content](#)

Deploy Workspace ONE UEM Applications

Configure Workspace ONE UEM Applications to deploy as public apps.

Utilize this simplified deployment workflow to seamlessly push Workspace ONE UEM applications to end users.

- 1 Navigate to **Apps & Books > Applications > Native > Public**.
- 2 Select **Add Application**.
- 3 Configure the fields on the screen that appears:

Setting	Description
Managed By	View the organization group the application uploads in.
Platform	Choose the appropriate platform.
Name	Enter a descriptive name in the field to help search for the application in an app store.
Search App Store	Select to search for the application in the app store. In order to search the Google Play Store in an on-premises deployment, you must integrate a Google Account with the Workspace ONE UEM MDM environment.

- 4 Review the information that automatically populates in the **Info** tab.

- 5 Add smart groups from the **Assignment** tab.
- 6 Use the **Deployment** tab to determine how your end users receive the app. End users find and download recommended apps in the app store. To make finding and deploying it easier, you can recommend it through Workspace ONE UEM or automatically push it to your devices.
- 7 Assign **Terms of Use**, if desired.
- 8 **Save and Publish.**

Overview for Onboarding VMware Workspace ONE Content

Onboarding requires end users to review and acknowledge training materials and videos before gaining full access to VMware Workspace ONE Content on their devices.

Single App Mode

Maximize Onboarding functionality, by configuring required content and pushing a single app mode profile to end-users devices. Once Onboarding completes, remove the profile to allow end users to access full device functionality.

Alternatively, configure Onboarding without single app mode to provide a more flexible experience for end users. In this set up end users cannot access the Workspace ONE Content until they view the required content, but they can still use their device.

	With Single App Mode	Without Single App Mode
VMware Workspace ONE Content	Locked in the Required Content View	Locked in the Required Content View
Other Device Apps	Inaccessible. The device remains locked in the Required Content View.	Accessible. End users can still use their devices.

User Experience

Before you enforce content viewing, consider how these choices affect the end-user experience. For example, pushing required content to a device out in the field might confuse end users, resulting in help desk tickets. In general, on-boarding, or in a similar guided scenario, provides an appropriate level of context for the limited device behavior, reducing the likelihood of end-user confusion.

Also, consider the impact of deploying Workspace ONE Content in single app mode, as it restricts device functionality to a single app, in this case, Workspace ONE Content. If planning to remove the single app mode restriction at a set time, ensure that the end users does not access other apps. Also, ensure that the end users perform work related tasks on their devices while their devices are restricted.

Enable Onboarding for VMware Workspace ONE Content

Onboarding provides a deployment option for Workspace ONE Content that locks the app into a view that only displays the required content until that content is viewed.

To enable onboarding:

- 1 Meet minimum OS and app requirements.
- 2 Determine and configure enrollment flow.
- 3 Navigate to **Content > Settings > Advanced > Onboarding**.
- 4 Set **Onboarding** to **Enabled** and configure the settings that appear.

Setting	Description
Administrative Unlock Code	Set this code to override the supervised mode as an admin.
Entrance Message	Provide a message to end users explaining that they must view the required content before they can use their device.
Exit Message	Provide a message to end users explaining they viewed all the require content and are now free to use their device.

- 5 Select **Save**.

Content Management using Workspace ONE Console

10

The Content Management solution provides you multiple options to manage the content that is stored, synced, or deployed from the Workspace ONE UEM console.

Features

The Content Management solution provides the following functionalities to manage the content:

- Content Management Dashboard for quick overview of the users and managed content.
- List View for viewing and managing the content.
- Content Settings menu to configure repository, storage, deployment, and management options for different types of content.

For more information about Content Management options and different settings available to manage content deployed from the UEM console, see [Mobile Content Management Dashboard](#) and [Settings for Content Management](#).

This chapter includes the following topics:

- [Menu Options for Content Management](#)
- [Mobile Content Management Dashboard](#)
- [Content Management List View](#)
- [Options for Content Management](#)
- [Settings for Content Management](#)

Menu Options for Content Management

In addition to the default view in the console, there are several other screens that simplify content management. They display in a secondary navigation menu to the left of the Content Dashboard in the UEM console.

Review the available menu options for Content Management.

Setting	Description
List View	Toggle between the AirWatch Managed and Corporate File Server list view.
Repositories	Select repositories for accessing the repository configuration options. There are two types of repositories, admin added repositories and user added repositories. Users add repositories using the templates you configure in the console.
Categories	Add categories and subcategories. Added categories are displayed on the screen in a list view with an action menu.
Featured Content	Manage the featured content you added from the List View or the Categories List View on this screen. Featured content is displayed prominently within the VMware Workspace ONE Content, providing easy access to high volume content. Use this screen to control the order in which featured content is displayed in the Workspace ONE Content using drag or deleting irrelevant content.
Batch Status	Perform a Batch Import and review the details of your uploaded batch from this screen.
Settings	Select to access content specific settings.

Mobile Content Management Dashboard

View and manage the general content status of your device fleet from the Content Management Dashboard, the default content view. Use this centralized page in the console to gain immediate insights about users, to analyze the content for making business decisions, and to act on warnings.

Following are the different views and parameters that are displayed on the dashboard.

Setting	Description
Storage History	Overview storage quotas using the six-bar graphical summary.
User/Content Status	Summarize device content compliance at a glance using the status icon graphics. Each graphic fills to represent the percentage of devices or files that are in trouble. Select these icons to view devices that are out of compliance and to take administrative action.
Content Engagement	Learn which documents are the most useful and in-demand for your end users and the documents that you might consider deprecating. Select the displayed information to navigate directly to a page where you can edit your content.
User Breakdown	Information about end-user activity Today, This Week, or This Month. The icons represent your end users and are filled in with the percent of end users who are active.

Content Management List View

Act on the uploaded AirWatch Managed and synced Corporate File Server content from the Workspace ONE UEM console Content List View. The Content List View populates with the information you entered while uploading your content or repositories, providing an overview of all content.

Access this list by navigating to **Content > List View**.

Setting	Description
AirWatch Managed	View and manage the content you directly added to the UEM console in this default list view.
AirWatch Managed Menu	Act on AirWatch Managed Content using the available list view options. <ul style="list-style-type: none"> ■ Add Content – Select to add AirWatch Managed Content to the UEM console. ■ Storage Used – Review the status bar to see the percentage of allotted storage consumed by end users.
Corporate File Servers	View and manage synced repositories in this list view, or use the content list views for individual repositories.
Corporate File Servers Menu	To display configured repositories in the list view, select Show Repositories
Filter	Find desired documents using the available filters. <ul style="list-style-type: none"> ■ Category – Filter content using the categories assigned from the UEM console. ■ Type – Filter content based on the file type. ■ Expiration Status – Filter content to display only the content set to expire in 14 days.
Active/Inactive	Information about the content availability to end users. <ul style="list-style-type: none"> ■ Green circles display next to active content. ■ Red circles display next to inactive content. Inactive content is not searchable, viewable, or sent automatically to devices.
Name	Select to edit the general Info , Details , Previous Version , Security , Assignment , and Deployment information you configured when adding your content. You can also download or delete previous content versions.
Action Menu	Manage your content using the available menu options. The two Content List View action menus differ slightly.

Options for Content Management

Use these options to manage uploaded or synced content and metadata in List View and other menus on Workspace ONE UEM console.

Action	AirWatch Managed	Corporate File Servers	Automatic Template	Manual Template	User-Added Repository	Category
Edit						
Manage file settings on an individual basis. Edited settings only affect the individual file, not the entire repository's settings.	✓	✓	✓	✓	✓	
Download a local copy of a previous file version.	✓					
Delete a previous file version from the console.	✓					
Update an existing file with a new version, archiving the original file.	✓					
Delete						
Remove a file from the UEM Console.	✓					

Action						
Remove file metadata from the UEM Console.	✓	✓	✓	✓	✓	
Initiate a manual sync between the network content and AirWatch.	✓	✓	✓	✓	✓	
Remove an empty subcategory or empty category from the UEM Console.						✓
Add						
Update an existing file with a new version, archiving the original file.	✓					
Add a subcategory to a category.						✓
Sync						
Initiate a sync between Workspace ONE UEM and integrated Corporate File Servers.	✓	✓	✓	✓	✓	
View Devices						
Open a device list, view the device an individual file is assigned to.	✓	✓	✓	✓	✓	
Push an individual file to a selected device.	✓	✓	✓	✓	✓	
Remove an individual file from a selected device.	✓	✓	✓	✓	✓	
Additional Options						
Add a file to Featured Content so that the file displays prominently within the VMware Workspace ONE Content.	✓	✓	✓	✓	✓	✓
Download a local copy of the file.	✓	✓	✓	✓	✓	
Remove a file from the UEM Console.	✓					
Remove file metadata from the UEM Console.		✓	✓	✓	✓	

Settings for Content Management

Content Management settings consist of various configurations related to content management.

To access the menu of available configurations, select **Settings**.

Setting	Description
Applications	Access the configuration screens for VMware Workspace ONE Content and VMware Content Locker Sync.
Content Gateway	Configure Content Gateway and download the installer.
Personal Content	Enable and configure Personal Content settings for end users.
User Storage	Configure storage quota exceptions for individual users. These exceptions provide the most granular level of storage assignment, and override organization or user group configurations set in Personal Content.
Remote Storage	Configure Remote File Storage and download the installer

Setting	Description
Content Viewer	Configure Content Rendering Engine and download the installer.
Advanced	Configure file type restrictions, on-boarding and requiring content for on-boarding, and integrating with a third-party e-Signature vendor.