

vRealize Network Insight Command Line Interface Guide

VMware vRealize Network Insight 3.3

vmware[®]

You can find the most up-to-date technical documentation on the VMware Web site at:

<https://docs.vmware.com/>

The VMware Web site also provides the latest product updates.

If you have comments about this documentation, submit your feedback to:

docfeedback@vmware.com

Copyright © 2017 VMware, Inc. All rights reserved. [Copyright and trademark information.](#)

VMware, Inc.
3401 Hillview Ave.
Palo Alto, CA 94304
www.vmware.com

Contents

About vRealize Network Insight Command Line Interface User Guide	5
1 Log in to the vRealize Network Insight CLI	7
2 vRealize Network Insight CLI Commands	9
help	10
show-service-status	10
set-web-proxy	11
logout	11
nslookup	11
ping	12
telnet	12
setup	13
services	14
support-tunnel	15
offline-registration	15
show-config	16
show-connectivity-status	16
set-proxy-shared-secret	16
support-bundle	17
log-trace	17
disk-usage	18
logs-to-cloud	18
package-installer	19
tool-manager	19
vrni-proxy	20
show-version	20
telemetry	21
modify-password	21
custom-cert	21
appliance-reboot	22
traceroute	22
set-banner	23
Index	25

About vRealize Network Insight Command Line Interface User Guide

The vRealize Network Insight Command Line Interface User Guide provides information on Command Line Interface (CLI) to manage the Proxy and Platform configuration. The CLI includes an auto-complete feature that recognizes a command by its initial characters and completes the command when you press the Tab key. Each command has a -h option parameter that provides information on that command.

Intended Audience

This information is intended for administrators or specialists responsible for using vRealize Network Insight command line interface. The information is written for experienced virtual machine administrators who are familiar with enterprise management applications and datacenter operations.

VMware Technical Publications Glossary

VMware Technical Publications provides a glossary of terms that might be unfamiliar to you. For definitions of terms as they are used in VMware technical documentation, go to <http://www.vmware.com/support/pubs>.

Log in to the vRealize Network Insight CLI

1

vRealize Network Insight provides CLI login credentials using Secure Socket Shell (SSH) client or the console.

Log into the command line interface.

Procedure

- 1 Type *consoleuser* as the user name.
- 2 Type *ark1nc0ns0l3* as the password.

vRealize Network Insight CLI Commands

2

This reference includes examples for syntax information for each command.

This chapter includes the following topics:

- [“help,”](#) on page 10
- [“show-service-status,”](#) on page 10
- [“set-web-proxy,”](#) on page 11
- [“logout,”](#) on page 11
- [“nslookup,”](#) on page 11
- [“ping,”](#) on page 12
- [“telnet,”](#) on page 12
- [“setup,”](#) on page 13
- [“services,”](#) on page 14
- [“support-tunnel,”](#) on page 15
- [“offline-registration,”](#) on page 15
- [“show-config,”](#) on page 16
- [“show-connectivity-status,”](#) on page 16
- [“set-proxy-shared-secret,”](#) on page 16
- [“support-bundle,”](#) on page 17
- [“log-trace,”](#) on page 17
- [“disk-usage,”](#) on page 18
- [“logs-to-cloud,”](#) on page 18
- [“package-installer,”](#) on page 19
- [“tool-manager,”](#) on page 19
- [“vrni-proxy,”](#) on page 20
- [“show-version,”](#) on page 20
- [“telemetry,”](#) on page 21
- [“modify-password,”](#) on page 21
- [“custom-cert,”](#) on page 21

- [“appliance-reboot,”](#) on page 22
- [“traceroute,”](#) on page 22
- [“set-banner,”](#) on page 23

help

This reference includes examples for syntax information for help command.

Table 2-1. help

Command	Description	Usage	Examples
help	Displays a list of commands with a short description about their use.	To view the list of commands without short description, use the -a flag.	help help -a

show-service-status

This reference includes examples for syntax information for show-service-status command.

show-service-status

Command	Description	Usage	Examples
show-service-status	Shows the status of all vRealize Network Insight services running on the PLATFORM or PROXY VMs.		PLATFORM- (cli) show-service-status ElasticSearch is running. HMaster is running. HRegionServer is running. Kafka is running. QuorumPeerMain is running. QuorumPeerMain is running. ResourceManager is running. NodeManager is running. restapilayer is running. SaasListener is running. SamzaAppMaster is running. SamzaContainer is running. Launcher is running. postgresql is running. nginx is running. patroni is running. QuorumPeerMain is running. All required services are running. QuorumPeerMain is running. QuorumPeerMain is running. QuorumPeerMain is running. QuorumPeerMain is running. PROXY- (cli) show-service-status CollectorMain is running. IpfixProcessor is running. postgresql is running. nginx is running. nfcapd is running.

set-web-proxy

This reference includes examples for syntax information for `set-web-proxy` command .

Table 2-2. set-web-proxy

Command	Description	Usage	Examples
<code>set-web-proxy</code>	Enables or disables the Web proxy or shows the status of the Web proxy.	<code>set-web-proxy [--ip IP] [--port PORT] {enable,disable,show}</code>	<code>set-web-proxy enable --ip-fqdn "x.y.local" --port 8080</code>

Syntax

Flag	Description
<code>--ip</code>	IP address to enable the Web proxy.
<code>--port</code>	Port number to enable the Web proxy.
<code>enable disable show</code>	Enables or disables or displays the configuration settings.

logout

This reference includes examples for syntax information for `logout` command.

Table 2-3. logout

Command	Description	Usage	Examples
<code>logout</code>	Exits from the interactive shell of the CLI.		

nslookup

This reference includes examples for syntax information for `nslookup` command.

Table 2-4. nslookup

Command	Description	Usage	Examples
<code>nslookup</code>	Queries Internet name servers interactively.	<code>nslookup FQDN</code>	<code>nslookup example.com</code>

Syntax

Flag	Description
<code>fqdn</code>	Server name to query such as <code>example.com</code> .

Related Commands

Command	Description
<code>ping</code>	Pings a machine.
<code>telnet</code>	Tests whether a specific TCP port is open.
<code>traceroute</code>	Prints route IP packets sent to a remote host.

ping

This reference includes examples for syntax information for ping command.

Table 2-5. ping

Command	Description	Usage	Examples
ping	Pings a host.	ping host	ping example.com

Syntax

Flag	Description
host	IP address or FQDN of the host to ping.

Related Commands

Command	Description
nslookup	Queries Internet name servers interactively.
telnet	Tests whether a specific TCP port is open.
traceroute	Prints route IP packets sent to a remote host.

telnet

This reference includes examples for syntax information for telnet command.

Table 2-6. ping

Command	Description	Usage	Examples
telnet	Test whether a specific TCP port is open. This command is for interactive communication with the host on a particular port number. PORT is an optional parameter. You must provide a host other than localhost or 127.0.0.1.	telnet host port	telnet 192.168.0.59 80 telnet example.com 80

Syntax

Flag	Description
host	IP address or FQDN of the host to ping.
port	Port number of the host.

Related Commands

Command	Description
nslookup	Queries Internet name servers interactively.
telnet	Tests whether a specific TCP port is open.
traceroute	Prints route IP packets sent to a remote host.

setup

This reference includes examples for syntax information for setup command.

Table 2-7. setup

Command	Description	Usage	Examples
setup	Sets up the network configuration. This command works in two modes: no arguments (default interactive) and with-ova-params. In the default interactive mode, no parameters are specified and multiple questions appear. In the with-ova-params mode, the command runs with parameters specified during OVA deployment. You can only change the IP address before the pairing of the Platform and Proxy. If the gateway IP subnet changes, you might need to reboot the VM.	setup [{with-ova-params}]	setup setup with-ova-params

Syntax

Flag	Description
-	<p>No parameters</p> <p>Running setup: Interactive Mode.</p> <p>Running setup: Interactive Mode.</p> <p>Warning!!!: Only selective configuration can be changed (y/n):y</p> <p>ovaops: configure deployed state</p> <p>Currently IP_Address = 192.168.21.56 , keep this (y/n)? [y]: n</p> <p>Enter new IP_Address (e.g. 192.168.0.10): 192.168.21.50</p> <p>Currently Netmask = 255.255.255.0 , keep this (y/n)? [y]: y</p> <p>Currently Default_Gateway = 192.168.21.1 , keep this (y/n)? [y]: y</p> <p>Currently DNS = 4.2.2.4 8.8.8.8 , keep this (y/n)? [y]: y</p> <p>Currently Domain_Search = [None] , keep this (y/n)? [y]: y</p> <p>Currently NTP = 0.pool.ntp.org 1.pool.ntp.org 2.pool.ntp.org 3.pool.ntp.org , keep this (y/n)? [y]: y</p> <p>Currently Rsyslog_IP = [None] , keep this (y/n)? [y]: y</p> <p>Currently Web_Proxy_IP = [None] , keep this (y/n)? [y]: y</p> <p>Currently Web_Proxy_Port = [None] , keep this (y/n)? [y]: y</p> <p>Currently Log_Push = True , keep this (y/n)? [y]: y</p> <p>y</p> <p>-----</p> <p>Received below values:</p> <p>-----</p> <p>IP_Address = 192.168.21.50</p> <p>Netmask = 255.255.255.0</p> <p>Default_Gateway = 192.168.21.1</p> <p>DNS = 4.2.2.4 8.8.8.8</p> <p>Domain_Search = [None]</p> <p>NTP = 0.pool.ntp.org 1.pool.ntp.org 2.pool.ntp.org 3.pool.ntp.org</p> <p>Rsyslog_IP = [None]</p> <p>Web_Proxy_IP = [None]</p> <p>Web_Proxy_Port = [None]</p> <p>Log_Push = True</p> <p>Configure and save configuration (y/n) [y]: n</p>
with-ova-params	Uses parameters passed during OVA deployment

services

This reference includes examples for syntax information for services command.

Table 2-8. services

Command	Description	Usage	Examples
services	Starts, stops, or restarts vRealize Network Insight services.	services {start,stop,restart}	services start services stop services restart

Syntax

Flag	Description
start stop restart	Starts, stops, or restarts the appliance service based on the parameter that you pass.

support-tunnel

This reference includes examples for syntax information for support-tunnel command.

Table 2-9. nslookup

Command	Description	Usage	Examples
support-tunnel	Enables, disables, or shows the status of the support tunnel.	support-tunnel {enable,disable,status}	support-tunnel enable support-tunnel disable support-tunnel status

Syntax

Flag	Description
enable disable status	Provides the status or enables or disables the support tunnel.

offline-registration

This reference includes examples for syntax information for offline-registration command.

Table 2-10. offline-registration

Command	Description	Usage	Examples
offline-registration	Generates offline registration request and applies provided response	offline-registration -h	offline-registration
offline-registration apply-response -h	To apply response, you have to pass the response	offline-registration apply-response [-h] response	

Syntax

Flag	Description
positional arguments: {generate-request,apply-response} sub-command help response	generate-request: output data needed to give to vmware support apply-response: apply response from vmware support response: Response string provided by VMware support
optional arguments: -h, --help	show this help message and exit

show-config

This reference includes examples for syntax information for show-config command.

Table 2-11. show-config

Command	Description	Usage	Examples
show-config	Shows the CLI configurations. Displays the CLI console banner, network configurations, and ova parameters.	show-config	(cli) show-config network configurations: IP Address: 192.168.21.55 Netmask: 255.255.255.0 Gateway: 192.168.21.1 DNS nameservers: 4.2.2.4 8.8.8.8 Domain Search list: arkin.net NTP servers: 0.pool.ntp.org 1.pool.ntp.org 2.pool.ntp.org 3.pool.ntp.org

show-connectivity-status

This reference includes examples for syntax information for show-connectivity-status command.

Table 2-12. show-connectivity-status

Command	Description	Examples
show-connectivity-status	Displays the connectivity status with all systems.	(cli) show-connectivity-status Platform VM Deployment ID: DOAR7MD Instance ID: IOAR7MT Created On: Sat Jul 23 00:39:57 UTC 2016 (1469234397) IP Address: 192.168.21.55 Netmask: 255.255.255.0 Gateway: 192.168.21.1 DNS nameservers: 4.2.2.4 8.8.8.8 NTP servers: 0.pool.ntp.org 1.pool.ntp.org 2.pool.ntp.org 3.pool.ntp.org Gateway ping status: Success Upgrade connectivity status: Passed Support connectivity status: Disabled

set-proxy-shared-secret

This reference includes examples for syntax information for set-proxy-shared-secret command.

Table 2-13. set-proxy-shared-secret

Command	Description	Examples
set-proxy-shared-secret	Configures the platform IP only on the Proxy VM.	set-proxy-shared-secret {secret}

Syntax

Flag	Description
secret	Secret key that the platform interface generates.

support-bundle

This reference includes examples for syntax information for support-bundle command.

Table 2-14. support-bundle

Command	Description	Usage	Examples
support-bundle	Provides support related logs for debugging.	support-bundle [-h] {list,create,delete,copy}	

Syntax

Flag	Description
list	Lists all support bundles created so far. Example: support-bundle list
create	Creates a support bundle to be shared for debugging. Example: support-bundle create
delete	Deletes specific or all bundle files. Example: To delete a specific bundle file: support-bundle delete --bundle DOAUAAO-IOAUACW-07252016-162328 To delete all bundle files: support-bundle delete
copy	SCP to any host for sharing with the support team. Example: support-bundle copy --user support --ip 192.168.1.1 --port 22 --bundle DOAUAAO-IOAUACW-07252016-162328 --targetpath /tmp

log-trace

This reference includes examples for syntax information for log-trace command.

Table 2-15. log-trace

Command	Description	Usage	Examples
log-trace	Displays a list of all log files and also component specific logs that help during debugging.	log-trace [-h] {list,grep, follow, display}	log-trace list log-trace follow /var/log/arkin/arkin_cli_install.log log-trace grep "ERROR" /var/log/arkin/arkin_cli_install.log log-trace display /var/log/arkin/arkin_cli_install.log 20 (to display last 20 lines)

Syntax

Flag	Description
list	Lists all log files that can be displayed and also lists the component specific logs. Example: log-trace list
follow	Usage: log-trace [-h] follow <file name> Example: log-trace follow /var/log/arkin/arkin_cli_install.log
grep	Usage: usage: log-trace grep [-h] pattern filename Example: log-trace grep "ERROR" /var/log/arkin/arkin_cli_install.log
display	Usage: usage: log-trace display [-h] filename numlines Example: log-trace display /var/log/arkin/arkin_cli_install.log 20 (to display last 20 lines)

disk-usage

This reference includes examples for syntax information for disk-usage command.

Table 2-16. disk-usage

Command	Description	Usage	Examples
disk-usage	Displays current disk partition disk usage statistics.	disk-usage	disk-usage

logs-to-cloud

This reference includes examples for syntax information for logs-to-cloud command.

Table 2-17. logs-to-cloud

Command	Description	Usage	Examples
logs-to-cloud	Enables, disables or displays status of the logs that are pushed to the cloud.	logs-to-cloud [-h] {show,enable,disable}	logs-to-cloud enable logs-to-cloud disable logs-to-cloud status

Syntax

Flag	Description
enable disable status	Provides the status or enables or disables the logs that are pushed to the cloud.

package-installer

This reference includes examples for syntax information for `package-installer` command.

Table 2-18. package-installer

Command	Description
<code>package-installer</code>	Manage upgrade (offline)

Table 2-19. Usage

Command	Description
<code>package-installer copy --host <IP> --user <username> --path <bundle file absolute path></code>	Copy the bundle to vRNI Platform/Proxy
<code>package-installer upgrade -h --name</code>	Run the upgrade

Table 2-20. Example

Command
<code>package-installer copy --host 192.168.21.22 --user ubuntu --path /home/ubuntu/VMware-vRNI.3.1.0.1473143945.upgrade.bundle</code>
<code>package-installer upgrade [-h] --name NAME</code>

Syntax

Flag	Description
<code>--host</code>	IP address, where upgrade bundle is downloaded from VMware download portal. Upgrade bundle should be downloaded on any Linux machine from where the bundle can be scp to vRealize Network Insight Platform or Proxy.
<code>--user</code>	User, who can be used to authenticate the Linux machine.
<code>--path</code>	Source path where the bundle is downloaded from VMware portal on Linux Machine.
<code>--port</code>	(Optional) - In case ssh port on Linux machine running other than port 22.

tool-manager

This reference includes examples for syntax information for `tool-manager` command.

Table 2-21. tool-manager

Command	Description
<code>tool-manager</code>	Helps to run tool

Table 2-22. Usage

Command	Description
<code>tool-manager copy --host <IP> --user <username> --path <tool bundle file absolute path></code>	Copy the tool bundle to vRealize Network Insight Platform/Proxy
<code>tool-manager run --name <tool name></code>	Run tool

Table 2-23. Example

Command	
tool-manager copy --host 192.168.21.18 --user ubuntu --path /home/ubuntu/patch-online-upgrade-3.0.0_201609151002.bundle	
tool-manager run --name patch-online-upgrade-3.0.0_201609151002	
Syntax	
Flag	Description
--host	IP address, where upgrade bundle is downloaded from VMware download portal. Upgrade bundle should be downloaded on any Linux machine from where the bundle can be scp to vRealize Network Insight Platform or Proxy.
--user	User, who can be used to authenticate the Linux machine.
--path	Source path where the bundle is downloaded from VMware portal on Linux Machine.
--port	(Optional) - In case ssh port on Linux machine running other than port 22.

vrni-proxy

This reference includes examples for syntax information for vrni-proxy command.

Table 2-24. vrni-proxy

Command	Description
vrni-proxy	vRealize Network Insight proxy managing utility

Table 2-25. Example

Command
ONSAAS: vrni-proxy set-platform --ip-or-fqdn 192.168.10.12
ONPREM: vrni-proxy set-platform --ip-or-fqdn platform.exampledomain.com
vrni-proxy platform-pair-status

Table 2-26. Syntax

Flag	Description
--ip-or-fqdn	Provide IP Address if Platform is onprem Provide FQDN if Platform is onsaas

show-version

This reference includes examples for syntax information for show-version command.

Table 2-27. tool-manager

Command	Description
tool-manager	Displays current version

Table 2-28. Usage

Command	Description
show-version	Show current vRealize Network Insight version

telemetry

This reference includes examples for syntax information for `telemetry` command.

Table 2-29. telemetry

Command	Description	Usage	Examples
telemetry	Enables, disables, or shows the status of the system health data collection	telemetry {enable,disable,show}	telemetry enable telemetry disable telemetry show

Table 2-30. Syntax

Flag	Description
enable disable show	Provides the status or enables or disables the system health data collection.

modify-password

The `modify-password` command is used to reset the password of the UI or the system user.

Table 2-31. modify-password

Command	Description	Usage	Examples
modify-password	Reset the password of the UI or the system user (cli) modify-password [-h]	modify-password [-h] {system, ui}	modify-password system modify-password ui

Table 2-32. Syntax

Flag	Description
positional arguments: {system, ui}	Example invocations: modify-password ui [-h] --user USER
optional arguments: -h, --help	modify-password system [-h] --user {support,consoleuser}

custom-cert

This reference includes examples for syntax information for `custom-cert` command.

Table 2-33. custom-cert

Command	Description	Usage	Examples
custom-cert	Applies custom certificate for UI access	custom-cert [-h] {copy,apply,list,remove,display}	custom-cert list custom-cert apply custom-cert display custom-cert remove

Syntax

Flag	Description
positional arguments: {copy, apply, list, remove, display}	copy – copies file locally using scp Example of copy: (cli) custom-cert copy --host "10.1.1.1" --user "adminxyz" --port 22 --path "/tmp/file.crt" (cli) custom-cert copy --host "10.1.1.1" --user "adminxyz" --port 22 --path "/tmp/file.key" apply – recertifies setup with new certificate list – lists custom certificate remove – removes custom certificate display – displays custom certificate details

appliance-reboot

This reference includes examples for syntax information for `appliance-reboot` command.

Table 2-34. appliance-reboot

Command	Description	Usage	Examples
appliance-reboot	Reboots the appliance	appliance-reboot [-h] {now}	appliance-reboot now

Syntax

Flag	Description
positional arguments: {now}	Used to avoid accidental invocation.

traceroute

This reference includes examples for syntax information for `traceroute` command.

Table 2-35. traceroute

Command	Description	Usage	Example
traceroute	Prints route IP packets sent to a remote host for the host that you provide as the parameter.	traceroute host	traceroute examples.com

Syntax

Flag	Description
host	Name of the host such as <code>example.com</code> .

Related Commands

Command	Description
nslookup	Queries Internet name servers interactively.
telnet	Tests whether a specific TCP port is open.
traceroute	Prints route IP packets sent to a remote host.

set-banner

This reference includes examples for syntax information for set-banner command.

Table 2-36. set-banner

Command	Description	Usage	Examples
set-banner	Sets the ssh banner. Sets the post-login banner for consoleuser	set-banner [-h] {support,consoleuser } banner	set-banner support "Text" set-banner consoleuser "Text"

Syntax

Flag	Description
positional arguments: {support,consoleuser} banner	Example invocations: (cli) set-banner support "This is a ssh banner.\nRestricted access only!!" Successfully set banner!
Quoted text with \n for new line	(cli) set-banner consoleuser "This is a post-login banner for consoleuser" Successfully set banner! (cli) logout # ssh support@10.126.55.193 This is a ssh banner. Restricted access only!! support@10.126.55.193's password: # ssh consoleuser@10.126.55.193 This is a ssh banner. Restricted access only!! consoleuser@10.126.55.193's password: This is a post-login banner for consoleuser (cli)

Index

A

appliance-reboot **22**

C

custom-certcustom **21**

D

disk-usage **18**

G

glossary **5**

H

help **10**

I

intended audience **5**

L

log-trace **17**

login **7**

logout **11**

logs-to-cloud **18**

M

modify-password **21**

N

nslookup **11**

O

offline-registration **15**

P

package-installer **19**

ping **12**

S

services **14**

set-banner **23**

set-proxy-shared-secret **16**

set-web-proxy **11**

setup **13**

show-config **16**

show-connectivity-status **16**

show-service-status **10**

show-version **20, 21**

T

telnet **12**

tool-manager **19**

traceroute **22**

V

vrni-proxy **20**

